

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

RECEIVED

FEB - 6 1951

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

February 1, 1951

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation W. E. Mathers Well No. 1 in the  
Company or Operator Lease

C/SE/4 NE/4 of Sec. 3, T. 12-S, R. 33-E, N. M. P. M.,  
Bagley-Siluro/Navonian Field Lea County.

The dates of this work were as follows: February 1, 1951

Notice of intention to do the work was ~~CHECKED~~ submitted on Form C-102 on January 29, 1951  
and approval of the proposed plan was ~~NOT OBTAINED~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10,964' - Total Depth - Line. Ran Temperature Survey - top of cement on outside of 5-1/2" casing; at 7494', ratio of actual to calculated fill 76.2%. Ran 2-3/8" O.D. EUE Tubing & 4-3/4" bit & checked top of cement at 10845'. Tested casing & connections with 1200# for 1/2 hour - no pressure drop. Drilled cement plug from 10845' to 10934' & washed from 10934' to 10964'. Open hole from 10934' to 10964'. Continued with completion operations.

Witnessed by K. V. Stephenson Amerada Petroleum Corporation Foreman  
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

5th day of February, 1951

Name Don TippPosition Assistant District Superintendent

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires 10-11-54Address Drawer D, Monument, New Mexico

Remarks:

FEB - 6 1951

Date

May [Signature]  
Oil & Gas Inspector

Title