OIL CONSERVATION COMMISCON

SANTA FE. NEW MEXICO

Miscellaneous Reports on W

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days that the specified is completed. It should be signed and sworn to before a notary public for reports on beating operations, results of shooting well, results of test of casing shut off, result of plugging of well, and ther important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

	V 31 A		ort by checking below.		
		e nature or rep			
REPORT ON BEGIN	NNING DRILLING		REPORT ON REP.	AIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL			REPORT ON PULI	ULLING OR OTHERWISE CASING	
SHUT-OFF	LT OF TEST OF CASIN	TG X	REPORT ON DEE	PENING WELL	
EPORT ON RESU	LT OF PLUGGING OF	WELL			
			April 4, 1951	Monument, N	ew Mexico
		••••••••••••	Date		Place
IL CONSERVATIO ANTA FE, NEW Mentlemen:	EXICO.	he results obta	ined under the heading n	oted above at the	
serada Petrole			Lease		
/SE/4 SE/4	of Sec	3	т. 12-3	R 33-1	, N. M. P. M.,
he dates of this wo	rk were as follows:	ril 2, 195	1		
			d on Form C-102 on		
of came	opth - 9410' Dril mt on outside of	led Out De 5-1/2" cas	t done and results oth - Lime. Ren ing at 5922 rat	Temperature Sur Le of actual to	• calculated
of come fill 88 at 9371 drop. with 10 ations.	epth - 9410' Dril mt en eutside ef .6%. Ran 2-3/8" '. Tested casing Drilled coment pl 00# for 1/2 hour . Stephensen	led Out De 5-1/2" cas O.D. MUE T & cennect ug frem 93 - ne press	pth - Lime. Ram ing at 5922', rat: ubing & 4-3/4" bit iens with 1000# fo 71' to 9410' & te ure drop. Centim	Temperature Sur ie of actual to the checked to or 1/2 hour - 1 sted casing & c ued with comple	o calculated p of cement no pressure connections
of come fill 88 at 9371 drop. with 10 ations.	epth - 9410' Dril mt en eutside ef .6%. Ran 2-3/8" '. Tested easing Drilled eament pl 00# for 1/2 hour	led Out De 5-1/2" cas O.D. MUE T & cennect ug frem 93 - ne press	pth - Lime. Ran ing at 5922', ratsubing & 4-3/4" bisiens with 1000# for 71' to 9410' & teare drep. Centing	Temperature Sur ie of actual to the checked to or 1/2 hour - 1 sted casing & c ued with comple	o calculated p of cement no pressure connections stiens oper-
of emerical states of emerical s	epth - 9410' Dril mt en eutside ef .6%. Ran 2-3/8" '. Tested casing Drilled coment pl 00# for 1/2 hour . Stephensen	led Out De 5-1/2" cas 0.D. EUR T & connect ug frem 93 - ne press	pth - Lime. Ram ing at 5922', rat: ubing & 4-3/4" bit iens with 1000# fo 71' to 9410' & te ure drop. Centim	Temperature Sur is of actual to the checked to or 1/2 hour - 1 ated casing & cu ued with comple ation For	o calculated p of cement no pressure connections etions oper-
of emaching of emaching still 88 at 9371 drop. with 10 atlens.	epth - 9410' Dril nt en outside of .6%. Ran 2-3/8" '. Tested easing Drilled cement pl 00% for 1/2 hour . Stephensen Name worn before me this	led Out De 5-1/2" cas 0.D. NUE T & connect ug from 93 - no press	pth - Lime. Rem ing at 5922', rat; ubing & 4-3/4" bit iens with 1000# fo 71' to 9410' & te ure drop. Centing Petroleum Cerper: Company I hereby swear or aff is true and correct.	Temperature Sur is of actual to the checked to or 1/2 hour - 1 ated casing & cu ued with comple ation For	o calculated p of cement no pressure connections stiens oper-
of emerical states of emerical s	epth - 9410' Dril nt en outside of .6%. Ran 2-3/8" '. Tested easing Drilled cement pl 00% for 1/2 hour . Stephensen Name worn before me this	led Out De 5-1/2" cas 0.D. EUR T & connect ug frem 93 - ne press	pth - Lime. Rem ing at 5922', rat; abing & 4-3/4" bit iens with 1000# for 71' to 9410' & te ure drep. Centim Petroleum Cerper Company I hereby swear or aff is true and correct. Name	Temperature Sur le of actual to the checked tep or 1/2 hour - 1 sted casing & co und with comple ation For	calculated p of cement no pressure connections stiens oper-
of emachill 88 at 9371 drop. with 10 atlens. Vitnessed by K. V	opth - 9410' Dril mt en outside of 66. Ran 2-3/8" '. Tested easing Drilled cement pl 00# for 1/2 hour . Stephensen Name worn before me this	led Out De 5-1/2" cas 0.D. EUR T & connect ug frem 93 - ne press Amerada	pth - Lime. Rem ing at 5922', rat; whing & 4-3/4" bit iens with 1000# for 71' to 9410' & te ure drep. Centim Petroleum Cerper Company I hereby swear or aff is true and correct. Name Position Assistan	Temperature Sur Le of actual to Le checked tep ur 1/2 hour - 1 sted casing & cued with comple ation Per Le District Super	calculated p of ement no pressure connections stiens oper- reman Title tion given above
of emaching states of emaching states at 9371 drop. with 10 atlens. Vitnessed by K. V. Subscribed and s	opth - 9410' Dril mt en outside of 66. Ran 2-3/8" '. Tested easing Drilled cement pl 00# for 1/2 hour . Stephensen Name worn before me this	led Out De 5-1/2" cas 0.D. NUE T & connect ug from 93 - no press	pth - Lime. Rem ing at 5922', rat; whing & 4-3/4" bit iens with 1000# for 71' to 9410' & te ure drep. Centim Petroleum Cerper Company I hereby swear or aff is true and correct. Name Position Assistan	Temperature Sur le of actual to the checked tep or 1/2 hour - 1 sted casing & co und with comple ation For	calculated p of ement no pressure connections stiens oper- reman Title tion given above
of emaching states of emaching states at 9371 drop. with 10 atlens. Vitnessed by K. V. Subscribed and states of emaching states at 9371 drop. with 10 atlens.	opth - 9410' Dril mt en outside of 66. Ran 2-3/8" '. Tested easing Drilled cement pl 00# for 1/2 hour Name Name Note Note	led Out De 5-1/2" cas 0.D. EUR T & connect ug frem 93 - ne press Amerada	pth - Lime. Rem ing at 5922', rat; abing a 4-3/4" bit iens with 1000\$ for 71' to 9410' a te ure drop. Centing Petroleum Cerper Company I hereby swear or aff is true and correct. Name Position Assistant Representing	Temperature Sur Le of actual to the checked tep ur 1/2 hour - 1 sted casing & co und with comple tion Poi tim that the informa the District Supe ada Potroleum	calculated p of cement no pressure connections stiens oper- reman Title tion given above
of emerical strains of the strains o	opth - 9410' Dril mt en outside of 66. Ran 2-3/8" '. Tested easing Drilled cement pl 00# for 1/2 hour Name Name Note Note	led Out De 5-1/2" cas 0.D. EUR T & connect ug from 93 - no press Amerada	pth - Lime. Rem ing at 5922', rat; abing & 4-3/4" bit iens with 1000# for 71' to 9410' & te ure drop. Centim Petroleum Cerper. Company I hereby swear or aff is true and correct. Name Position Assistant Representing Amer.	remperature Sur le of actual to the checked tep or 1/2 hour - 1 sted casing & casing	calculated p of cement no pressure connections stiens oper- Title tion given above printendent Corporation

and the second of the second o