

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

RECEIVED

SEP 24 1951

before the work specified is to
with any modifications considered
the Rules and Regulations of
HOBBES OFFICE

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	<input type="checkbox"/>	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	<input type="checkbox"/>	

Monument, New Mexico

Place

September 19, 1951

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Amerada Petroleum Corporation

W.E. Mathers

Well No. 3 in C/NW/4 SE/4

Company or Operator

Lease

of Sec. 3, T. 12-S, R. 33-E, N. M. P. M., Bagley-Pennsylvanian Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

9450' - Total Depth - Lime. Finished drilling 6-3/4" hole at 2:30 PM, 9/16/51.

Ran Schlumberger' Electrical, Gamma Ray & Microlog Surveys. Ran 340 Jts of 5 1/2" Casing as follows:

25 Jts 5 1/2" OD 17# Gr-8640 R-3 8-RT SS Csg. New (Conv) - - - 1023.91'
 114 Jts 5 1/2" OD 17# J-55 R-1 & 2 8-RT Italian Csg. New - - - 2482.36 (Short T&C)
 112 Jts 5 1/2" OD 15.5# J-55 R-2 8-RT Italian Csg. New, LT&C-- 3595.63
 66 Jts 5 1/2" OD 17# J-55 R-2 8-RT SS Italian Csg. New - - - 1378.05 (Short T&C)
 23 Jts 5 1/2" OD 17# Gr-8640 R-3 8-RT SS Csg. New (Conv) 955.18'
 340 Jts 9435.13'

Casing set at 9450' cemented with 600 sax slo-set cement mixed 3% Jel and 1/4" Flo-Seal per sack. Plug to 9365' @ 8:30 PM, 9/18/51. Max. Pump pressure 1400#. Ran 10 Baker Centralizers spaced 30' apart from 8990' to 9435' and 20 Weatherford Scratchers spaced 15' apart in above section. After W.O.C. approximately 24 hours we will test casing shut-off.

Approved SEP 24 1951, 19_____
except at follows:

Amerada Petroleum Corporation

Company or Operator

By Don Cooper
Position Assistant District Superintendent
Send communications regarding well to

Name Amerada Petroleum Corporation

Address Drawer D, Monument, New Mexico

OIL CONSERVATION COMMISSION,

By Roy Quirkrough
Title Oil & Gas Inspector

Journal of Management Studies, 19(1), 67-80.