



NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Company or Operator _____ Address _____
Well No. _____ in _____ of Sec. _____, T. _____
Lease _____ Field, _____ County. _____
R. _____, N. M. P. M., _____
Well is _____ feet south of the North line and _____ feet west of the East line of _____
If State land the oil and gas lease is No. _____ Assignment No. _____
If patented land the owner is _____, Address _____
If Government land the permittee is _____, Address _____
The Lessee is _____, Address _____
Drilling commenced _____ 19_____. Drilling was completed _____ 19_____.
Name of drilling contractor _____, Address _____
Elevation above sea level at top of casing _____ feet.
The information given is to be kept confidential until _____ 19_____.

OIL SANDS OR ZONES

No. 1, from _____ to _____ No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters — Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing _____, 19_____.
The production of the first 24 hours was _____ barrels of fluid of which _____% was oil; _____% emulsion; _____% water; and _____% sediment. Gravity, Be. _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

_____, Driller _____, Driller
_____, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this _____ day of _____, 19_____.

Notary Public
Place _____ Date _____
Name _____
Position _____
Representing _____
Company or Operator _____
Address _____

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
8810	8870	60	Drill Stem Test odor, fusilinids, black carbonaceous material associated with anhydrite 2 packers 630° WC 3 hrs. 5/8" BHC and 1" SC no mud, gas, oil or water to surface, Rec. 630° WC cut w/gas 210° heavy drlg. mud cut w/oil and gas BHFP 500#-500# 15 min S-I BHP 1600#, Hy Hd 5350# 5500#
8870	8871	1	No formation logged
8871	8913	42	Cored Rec. 12" 8871-8872-1/2 very fine crystalline dark brown dolomite with 1" to 4" anhydrite inclusions 8872-1/2 to 8875 very fine crystalline dark brown to black dolomite somewhat shaley, shale breaks at 8873 showing slickensides 8875-8877 very fine crystalline dark brown dolomite with a large anhydrite inclusions (6") from 8876 to 8876-1/2 bottom 4" mostly black shale with slickensides 8877 top of Penn 8877-8880-1/2 fine crystalline dark brown limestone trace fluorescence along stylolite 8880-1/2 to 8883 fine crystalline dark brown to black limey dolomite with 3" anhydrite inclusions trace fluorescence around anhydrite inclusion 1-1/2" @ 8940
8913	8942	29	Lime
8942	8948	6	Lime and chert
8948	8960	12	Lime
8960	8964	4	Lime and chert
8964	9087	123	Lime
9087	9105	18	Lime and shale
9105	9126	21	Lime
9126	9144	18	Lime and shale
9144	9236	92	Lime
9236	9254	18	Lime and shale
9254	9311	57	Lime
9311	9372	61	Lime and shale
9372	9393	21	Lime
9393	9407	14	Lime and shale
9407	9417	10	Lime and chert
9417	9479	62	Lime
5006	9479	4473	Ran Schlumberger
9479	9530	51	Lime
9530	9555	25	Cored Rec. 25-1/2" 9530-9533-1/2 fine crystalline gray limestone with 1/8" gray shale partings 9533-1/2 - 9535 alternating finely crystalline limestone and red and gray slightly calcareous shale layers 1/2" to 3" thick 9535-9536 soft black heaving shale 9536-9537-1/2 dark gray to black calcareous shale 9537-1/2 to 9540 dark reddish gray slightly calcareous shale 9540-9543 finely crystalline dark gray limestone with many gray and red calcareous shale partings, 1/32" to 1/2" thick 9543-9544 red and gray dense shale with a trace of red shale with limestone inclusions gray shale calcareous 9544-9550-1/2 dark gray finely crystalline limestone with numerous red and gray shale partings 9550-1/2 to 9553 finely crystalline gray limestone with red shale partings 9553-9555-1/2 alternating gray and yellow shale with finely crystalline gray limestone inclusions Rec. 20" 9555-9558-1/2 yellow, red and gray shale very soft disintegrating 9558-1/2 to 9563-1/2 finely crystalline gray limestone red shale mixed throughout 9563-1/2 to 9565-3/4 finely crystalline gray limestone stylolitic 9565-3/4 to 9566-3/4 finely crystalline limestone vuggy porosity 9566-3/4 to 9567 finely crystalline gray limestone 9567-9568 gray shale with some limestone inclusions and numerous fusilinids 9568-9575 finely crystalline gray limestone with gray shale mixed throughout more red at base
9555	9575	20	Cored
9575	9576	1	Shale and lime
9553	9576	23	Drill Stem Test 2 packers 630° WC 1 hr. 5 min 5/8" BHC and 1" SC no oil, gas, water or mud to