

50-025-02644

COUNTY	LEA	FIELD	Bough	OWWO	STATE	NM	MN	02649
OPR	MC GRATH & SMITH, INC.							MAP
	1 Federal "13"							
	Sec 13, T-9-S, R-35-E							CO-ORD
	660' FNL, 660' FWL of Sec.							
	Re-Spd 1-16-70							
	Re-Cmp 1-19-70							
	CLASS		EL					
	FORMATION	DATUM	FORMATION	DATUM				
CSG & SX - TUBING								
13 3/8" at 375' w/350 sx								
9 5/8" at 4433' w/1900 sx								
7" at 9615' w/1790 sx.								
LOGS	EL	GR	RA	IND	HC	A		
TD 9615'; PBD 9612'								
IP (Bough "C") Perfs 9585-9605' F 150 BOPD + 50 BW. Pot based on 24 hr test thru 28/64" chk, TP 375#.								

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	9600'	TYPE	WO
DATE				

F.R. 11-4-69
 PD 9600' WO (Bough "C")
 (Orig. Sharp Drlg. Co. #1 Federal "13", comp
 1-14-50 thru (Permo-Penn) Perfs 9585-9605',
 OTD 9615', OPB 9610'; OWWO & Re-Cmp 11-26-64
 as Pan American Pet. Corp. #1 Hood - Federal thru
 (San Andres) Perfs 4748-51', OTD 9615', OPB 4753')
 1-26-70 TD 9615'; PBD 9612'; COMPLETE
 Sqzd (4748-51')
 1-29-70 Cleaned out to 9612'
 COMPLETION REPORTED

COUNTY	LEA	FIELD	Bough-SA	STATE	N.M.	OWWO
OPR	PAN AMERICAN PETROLEUM CORP.					MAP
1 Hood-Federal						
Sec. 13, T-9-S, R-35-E					CO-ORD	
660' fr N & W Lines of Sec.						
Re-Spud 10-27-64						
Comp 11-22-64		CLASS		EL		
		FORMATION	DATUM	FORMATION	DATUM	
CSG & SK. TUBING						
13 3/8"	375'	350				
9 5/8"	4433'	1900				
7"	9615'	1790				
LOGS	EL	GR	RA	IND	HC A	
		TD 9615', PBD 4753'				

IP San Andres Perfs 4748-51' Flwd 380 MCFGPD + 5 BW. Pot. Based on 24 hr test thru 15/64" chk., FTP 400#.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	PB 4900'	TYPE
DATE			

F. R. 10-29-64; OWWO, OTD 9615'.
Orig. Sharp, J. R., #1 Yeckel.
PD 4900' - San Andres.

11-2-64 TD 9615', PB 4836', swbg.
Perf. @ 4848' w/4 shots.
Sq. Perfs. 4848' w/100 sx. DO 4836'
Perf. 4756-78', 4803-20' w/2 SPF
Ac. 3000 gals.
Swbd. 53 BLW + 64 BNW/9 hrs.

11-9-64 TD 9615', PB 4753', prep to perf.
Swbd. 247 BW/20 hrs.
Sq. Perfs. 4756-4820' w/200 sx. DO 4753'

11-16-64 TD 9615', PB 4753', tstg.
Perf. 4748-51' w/2 SPF.
Ac. 500 gals. & swbd. dry.
Re-Ac. 1000 gals. 4748-51'
Flow 320 MCFGPD + 24 BW thru 20/64" chk.

11-23-64 TD 9615', PBD 4753', COMPLETED.

IP San Andres Perfs 4748-51⁵, Flwd 530 MCFGPD + 4 BW. Pot.
Based on 24 hr. test thru 14/64" chk., FTP 540#.

CONT. _____ PROP DEPTH PB 4900' TYPE _____
DATE _____

F. R. 10-29-64; OWWO, OTD 9615'.
Orig. Sharp, J. R., #1 Yeckel.
FD 4900' - San Andres.
11-2-64 TD 9615', PB 4836', swbg.
Perf. @ 4848' w/4 shots.
Sq. Perfs. 4848' w/100 sx. DO 4836'.
Perf. 4756-78', 4803-20' w/2 SPF.
Ac. 3000 gals.
Swbd. 53 BLW + 64 BNW/9 hrs.
11-9-64 TD 9615', PB 4753', prep to perf.
Swbd. 247 BW/20 hrs.
Sq. Perfs. 4756-4820' w/200 sx. DO 4753'.
11-16-64 TD 9615', PB 4753', tstg.
Perf. 4748-51' w/2 SPF.
Ac. 500 gals. & swbd. dry.
Re-Ac. 1000 gals. 4748-51'.
Flow 320 MCFGPD + 24 BW thru 20/64" chk.

LEA Bough-SA N.M. OWWO Sec. 13-9S-35E
PAN AMERICAN PETROLEUM CORP. #1 Hood-Federal Page #2

11-23-64 TD 9615', FBD 4753', Completed.

11-30-64 This ticket replaces previous completion ticket
issued 11-23-64 amended information.