

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instruction on re-
verse side)Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 0450847
2. NAME OF OPERATOR McGrath & Smith, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -
3. ADDRESS OF OPERATOR 418 Bldg. of Southwest, Midland, Texas 79701		7. UNIT AGREEMENT NAME -
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit P, 660' FSL & 660' FEL, Section 13		8. FARM OR LEASE NAME Federal A-13
14. PERMIT NO. -	15. ELEVATIONS (Show whether DF, ST, CR, etc.) GL 4098, KB 4110	9. WELL NO. 3
		10. FIELD AND POOL, OR WILDCAT Bough Permo Penn
		11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Sec. 13, T9S, R35E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☒(Other) Well Record ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded re-entry at 3:30 p.m., 11-29-69.

Drilled out cement and mud with 6-3/4" bit to top of 5 1/2" liner @ 3946'.

Tested 7-5/8" casing to 2000 psi. - o.k. Cleaned out inside 5 1/2" liner with 4-3/4" bit from 3946 to 9636. PBDT now 9636.

Circ. hole with fresh water. Tested 5 1/2" to 2000 psi. - o.k.

Ran 2-3/8" tbg. - swabbed dry.

Acidized with 2000 gals. 15% NE on 12-7-69. Swab tested, on 12-17-69, pulled 2-3/8" tbg. and ran 2-7/8" tbg.

Ran 9573.78 of 2-7/8" EUE 8rd N80 Tbg. with fluid pack pump cavity and Guiberson RMC-1 pkr.

Tubing landed at 9583.78' with pkr. set at 9541.61'.

Installed hydraulic pumping equipment and began pumping on 12-25-69.

18. I hereby certify that the foregoing is true and correct

SIGNED J. TaylorTITLE Sup't.DATE 12-30-69

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

JAN 5 1970

*See Instructions on Reverse Side
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO