

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)FORM APPROVED  
Budget Bureau No. 42-R1424

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 0450847
2. NAME OF OPERATOR McGRATH & SMITH, INC.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -
3. ADDRESS OF OPERATOR 418 Bld. of Southwest, Midland, Texas 79701		7. UNIT AGREEMENT NAME -
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1980' FWL, Section 13		8. FARM OR LEASE NAME Federal A-13
14. PERMIT NO. -		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GL 4114, KB 4127		10. FIELD AND POOL, OR WILDCAT Bough Permo Penn
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 13, T9S, R35E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☒(Other) Well RecordREPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Rigged up - Spudded 11-12-69. Cleaned out inside 9-5/8 to top of 7" at 1726'. Then cleaned out inside 7" to 9500'. Tested 7" and 9-5/8" to 2000 psi. - o.k. Cleaned out inside 7" to 9597'. (Bottom of 7") and cleaned out in open hole to 9673'. Spotted 45 Sx. Class C Cement from 9673 to 9543. WOC 13 hours. Drilled out cement to 9615' in open hole. Ran 2-7/8 N80 Tbg. to 9582' with pkr. set at 9489'. Acid 500 gals. swbd. and flowed oil and water. Acid 2000 gals. swbd. and began flowing. Potential test 12-5-69. F.145 BO, 170 BW in 24 hours on 22/64 ck. TP 500, CP-Pkr. GOR 1869.

18. I hereby certify that the foregoing is true and correct

SIGNED J.B. TaylorTITLE Sup't.DATE 12-8-69

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

\*See Instructions on Reverse Side. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO