

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

July 25, 1962

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Socony Mobil Oil Company, Inc.

Hobbs Leonard

Well No. 1

in P

(Company or Operator)

SE 1/4 SE 1/4 of Sec. 14

T. 9 S

R. 35 E

NMPM,

Bough

(Unit)

Pool

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 9651'

FBTD: 9650'

Csg: 10 3/4" @ 465' w/450 sx., Circ.; 7 5/8" @ 4210' w/1630 sx, top cem. @ 825';
5 1/2" liner @ 9651' w/165 sx., top cem. 8155', top 5 1/2" liner @ 4035' squeezed
w/300 sx.

Perfs: 9618-9634'

Propose to move in pulling unit, remove Hydraulic pumping equipment & install BOP.
Run 2" tbg. to 9650' & circulate hole w/mud laden fluid. Squeeze perfs. 9618-9634
w/100 sx neat cement, top cement estimated @ 8650'. Pull tbg. to 4050' and spot
20" sx cement plug 4050-3950'. Remove well head connection & BOP. Spot 10" sx
cement plug in top of 7 5/8" csg. Spot 10" sx cement plug between 7 5/8" and 10 3/4"
casings at surface. Install regulation monument. Mud laden fluid between plugs.

Approved....., 19.....

Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Socony Mobil Oil Company, Inc.

(Company or Operator)

By.....

Position..... Senior Clerk

Send Communications regarding well to:

Name..... Socony Mobil Oil Company, Inc.

Address..... Box 2406, Hobbs, New Mexico