

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ANTA FE	
FILE	
J.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBES OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION

MAR 7 11 34 AM '67

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-10069-1	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Lone Star Producing Company		8. Farm or Lease Name King State
3. Address of Operator Box 4815, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 16 TOWNSHIP 9-S RANGE 35-E NMPM.		10. Field and Pool, or Wildcat Boughjink-San Andres Gas
15. Elevation (Show whether DF, RT, GR, etc.) 3,941' Ground		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to plug and abandon by spotting 50 sacks cement plug over perforations 4,915' to 4,840' and up to 4,690' (225'). Plug will be spotted through 2" tubing by displacement method. Load hole above plug with mud laden fluid. Spot 10 sack plug in top of 9-5/8" OD casing. Install 1/2" marker. Fill cellar and pits. Clean up location.

The 7" OD liner, 9-5/8" OD intermediate casing and 13-3/8" OD surface casing will be left in hole. Each string is circulated with cement.

We desire to begin plugging operations on or before March 15, 1967.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. J. Ince TITLE Dist. Prod. Supt. DATE March 6, 1967

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: