

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

1-9-59

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Magnolia-Glenm

J. E. Simmons

(Company or Operator)

Well No. 1 in M

(Unit)

SW  $\frac{1}{4}$  SW  $\frac{1}{4}$  of Sec. 21, T. 9S, R. 35E NMPM, West Crossroad San Andres Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This is the only well drilled and producing from this pool. Production from this well is no longer commercial, therefore; it will be plugged and abandoned. All offsetting acreage to this well is owned by the operator.

TD of this well is 4948' with 5 $\frac{1}{2}$ " 15.5# J-55 casing cemented on bottom. Plug back TD is 4878' with perforations 4801-4816 and 4835-4864:

We plan to pull some 2500' of 5 $\frac{1}{2}$ " casing from this well leaving 302' of 8 5/8" surface casing and 5 $\frac{1}{2}$ " from approximately 2500' to TD.

Cement plugs will be placed as follows: 25sx on bottom to cover perforations by some 100' 25sx across the top of 5 $\frac{1}{2}$ " casing left in hole, 25sx at surface casing shoe and 10sx at surface. An appropriate steel post monument will be set to mark the well site and location will be cleared.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

J. E. SIMMONS

Company or Operator

By..... (John C. Byers)

Position..... Engineer

Send Communications regarding well to:

Name..... John C. Byers

Address..... Great Plains Life Bldg., Lubbock, Texas