


MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO



MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

ed, and work should not begin until approval is obtaine the Commission. Indicate nature of	notice by checking below:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL		
Artes	ia, New Mexico August 24, 1948 Place Date	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen: Following is a notice of intention to do certain work as	described below at the	
		IE NW
	N. M. P. M., Wildest	Field.
Lea County.		
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at A Mudded from top of cement plug to 75 sack cement plug starting at A	2200† 2200†	
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at a Mudded from top of cement plug to 75 sack cement plug starting at a Mudded from top of cement plug to 15 sack cement plug starting at a Mudded to surface and put in 10 a	4100° 5 2200° 2200° 5 267° 234°	
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at a Mudded from top of cement plug to 75 sack cement plug starting at a Mudded from top of cement plug to 15 sack cement plug starting at a Mudded to surface and put in 10 a Confirming plugging conversation bet	(100) 0 2200) 2200) 0 267; 234) sack plug	
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at A Mudded from top of cement plug to 75 sack cement plug starting at A Mudded from top of cement plug to 15 sack cement plug starting at A Mudded to surface and put in 10 a Confirming plugging conversation bes	(100) 0 2200) 2200) 0 267; 234) sack plug	
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at A Mudded from top of cement plug to 75 sack cement plug starting at A Mudded from top of cement plug to 15 sack cement plug starting at A Mudded to surface and put in 10 a Confirming plugging conversation bes	4100: 0 2200: 0 267: 0 267: 0 34: 0 ack plug 0 ween Roy Yarbrough and Charlie Miller.	
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at a Mudded from top of cement plug to 75 sack cement plug starting at a Mudded from top of cement plug to 15 sack cement plug starting at a Mudded to surface and put in 10 a Confirming plugging conversation bet	Vickers Petroleum Company, In	
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at a Mudded from top of cement plug to 75 sack cement plug starting at a Mudded from top of cement plug to 15 sack cement plug starting at a Mudded to surface and put in 10 a Confirming plugging conversation bes	Vickers Petroleum Company, Ir Company or Operator By Position Authorized Agant Send communications regarding well to Name Vickers Petroleum Company, Position Authorized Agant Send communications regarding well to	· · · · · · · · · · · · · · · · · · ·
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at a Mudded from top of cement plug to 75 sack cement plug starting at a Mudded from top of cement plug to 15 sack cement plug starting at a Mudded to surface and put in 10 a Gonfirming plugging conversation bet AUG 3 0 1948 Approved Aug 3 0 1948	Vickers Petroleus Company, In Company or Operator By Position Authorized Agent Send communications regarding well to	· · · · · · · · · · · · · · · · · · ·
Well will be plugged as follows: Mudded back to 4100° from 5316° 25 sack cement plug starting at a Mudded from top of cement plug to 75 sack cement plug starting at a Mudded from top of cement plug to 15 sack cement plug starting at a Mudded to surface and put in 10 a Gonfirming plugging conversation bet AUG 3 0 1948 Approved Aug a follows:	Vickers Petroleus Company, In Company or Operator By Position Authorized Agant Send communications regarding well to Name Vickers Petroleus Company, Address 511 Missouri Street Roswell, New Mexico	· · · · · · · · · · · · · · · · · · ·