

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANITARY	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CHURN OR PUMP BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. Unit Agreement Name
2. Name of Operator Walter W. Anderson		8. Farm or Lease Name S. E. Anderson
3. Address of Operator Box 301, Caprock, New Mexico 88213		9. Well No. 1-Y
4. Location of Well UNIT LETTER J FEET FROM THE 1880 LINE AND 1980 FEET FROM THE 1900 LINE, SECTION 30 TOWNSHIP 93 RANGE 35E NMPH.		10. Field and Pool, or Wildcat Jenkins San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 4175 DF		12. County Log

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

July 31, 1978

Dumped by bailer, 35 sax of 15.8 lb. per. gal cement slurry around & above 9 5/8 casing stub at 646ft. GL. Let cement set 20 hr. found top at 608 ft. GL.

July 28, 1978

Dumped 11 bbl. 10 lb. brine with 25 lb. salt water gel to the bbl. ran a burley sack plug to top of brine & gel at 495 ft. GL. dumped 5 sax cement plug let set for 20 hr. found top at 485 ft.

July 29, 1978

Dumped 50 sax of 15.8 lb pr. gal. cement slurry, let set 40 hr., found top at 385 ft. GL.

July 31, 1978

Dumped 50 sax of 15.8 lb. per. gal. cement slurry, let set 48 hr., found top at 340 ft. in 13 3/8 casing.

Aug. 2, 1978

Bailed 13 3/8 surface pipe dry to 340 ft. GL., let set for 48 hr., ran bailer and found no fluid in the hole.

Aug. 5, 1978

Filled surface pipe with 50 bbl. brine and 25 lb. salt water gel to the bbl. Welded cap and marker to 13 3/8 casing, filled collar and cleaned well site.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Walter W. Anderson TITLE Owner/Operator DATE Aug 7, 1978

APPROVED BY Eddie Seay TITLE OIL & GAS INSPECTOR DATE JUL 1 1980

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

AUG 14 1978

OIL CONSERVATION COMM.
HOBBS, N. M.