F Elev. bing Diamete rforated Inter en Hole Inter Test Before orkover	val(s)	Tubing Depth Oil Production BPD	RESULTS C Gas Produ MCFP	Producin DF WORK	g Format OVER Water Pr		GOR Cubic feet/Bbl	Gas Well Potenti
bing Diamete rforated Inter	r val(s)		RESULTS C	Producin	g Format		Oil String	
bing Diamete rforated Inter	r val(s)	Tubing Depth			- i		Oil String	
bing Diamete	r	Tubing Depth		Oil Strin	-	er	Oil String	
		Tubing Depth		Oil Strin	g Diamet	l er	Oil String	
			PBTD	Oil String Diame		Producing	Interval	
		FILL IN BEL	OW FOR REM			PORTS O	NLY	······
itnessed by C. L. Sparkman			Position Field Supt.			Company HUMBLE OIL & REFINING COMPANY		
	Drille	od plug at 9:0	9 P.M. on :	11-25-6	1. Dr	illing.		
	Ran 42 at 429 2:30 F 31 hou	275' (133 Jts) O: Cement wi o.M. on 11-24- urs. Top of c casing w/100	of 8-5/8" th 500 saci 61. Cement sment at 30	casing (s reg t did n 200' by	, 24#, w/8% G ot cir temp	J-55, el. PO culate.	B at WOC	
Plugging etailed accou		nature and quantity of	nedial Work	d. and res	ults obta	ined		
	g Drilling Operati		sing Test and C				Explain):	
1-24, 11		Undesign	A REPORT OF	ildcat		County		
ate Work Per	eveler	Pool	1	<u> </u>	33	Township T-10		Range R-35-E
			Well No. U	Addre Be	a 2347	Hobbe	New Mexic	
HUMBLE	OIL & REFINI			· · · · · · · · · · · · · · · · · · ·		as per Cu	mmission Rule	1106)
ease	any	(Subm	t to appropria				••••••••••••	

1