Form C-103	DIL JONSERVATION COMMI, JION DECEMIN
	Santa Fo, New Mexico
0.1	DIL JONSERVATION COMMIL SION Santa Fe, New Mexice MSCELLANEOUS REPORTS ON WELLS report in triplicate to the Oil Conservation Commission or its proper agent within ten these after the work ammilited It should be signed and sworn to before a potary public for reports on beginning drilling oner-
ations, resul	report in triprovide to the All Lootservation Commission of its proper agent within ten trans after the work completed. It should be signed and sworn to before a notary public for reports on beginning drilling oper- ts of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed before a notary public. See additional instructions in the Rules and Regulations of the Commission.
	Indicate nature of report by checking below:
REPORT O	N BEGINNING DEILLING OPERA-

REPORT ON BEGINNING DRILLING OPERA- TIONS		REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	I	

	Brownfield. 7	etaz	April 21.]	1944
	•	Place	•	Date
OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO. Gentlemen:	٩,			
Following is a report on the work done	e and the results obta	ined under the headin	g noted above at	the
Company or Operator				
C SW SW	of Sec. <u>10</u>	, T. 11 S	_, R 35 R	
Wildost				
The dates of this work were as follows:				
Notice of intention to do the work was and approval of the proposed plan was	s (management) submitted	d on Form C-102 on	April 10]	

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 5505'. Heavy 11 lb. mud pumped into hode from bottom to 1948'. Cemented w/30 Sax from 1948' to 1852', in 8 5/8" Casing. Hole filled to heavy 11 Lb. mud. 8 5/8" Cag. shot at 445' and pulled out 445'. Spotted drill pipe at 300' and pumped in 25 Sax. cement. Hele filled w/ heavy 11 lb. mud. Hole bridged at 15' from top and 20' of 4" esg. cemented inside and out to surface of ground, 311' of surface pipe sirculated w/235 Sax. to protect surface water. Cellar filled w/ cement. 4" marker set in empent.

Witnessed by1	Name Name	Company	Title	
Subscribed and swor	m before me this 21st	I hereby swear or affirm that the information given above is true and correct.		
day of	April , 19 44	Name CE day G	<u><</u>	
the Kat	let	Position District Superinten	lent	
	Notary Public	Representing Magnolia Potro Company or Operato		
My commission expir	es June 30, 1945	Address	field, Texas	
Remarks:		Roy yo	rest soros Title	

stist v K of des 2

n ^{an} san an taon an tao

1