

Date	Make	Pkr Depth	Hole Size	Csg Seat	Size Top	Choke Bot.	Tool Open	Tested
2-24-49	Halliburton	4599	8-3/4	4227	1"	5/8"	22 min.	4599-4695, rec 5' dsl mud
2-27-49	"	5050	8-3/4	4227	1"	5/8"	23 min.	5050-5080, rec 5' dsl mud
4-14-49	"	9040	8-3/4	4227	1"	5/8"	38 min.	9040-9096, rec 15' dsl mud
4-16-49	"	9170	8-3/4	4227	1"	5/8"	92 min.	9170-9208, rec 60' dsl mud & slight show of oil
4-24-49	"	9468	8-3/4	4227	1"	5/8"	60 min.	9468-9514, rec 10' dsl mud
5-5-49	"	9769	8-3/4	4227	1"	5/8"		9769-9923, no test pkr failed
5-6-49	"	9781	8-3/4	4227	1"	5/8"	75 min.	9781-9950, rec 62' dsl mud
5-9-49	"	10047	8-3/4	4227	1"	5/8"	60 min.	10047-10088, rec good blow of gas w/oil
5-11-49	"	9970	8-3/4	4227	1"	5/8"	536 min.	9970-10089, rec 630' clean oil 8590' oil & gas out salt water
5-13-49	"	10077	8-3/4	4227	1"	5/8"	205 min.	10077-10144, rec 300' dsl mud.
7-8-49	"	12249	8-3/4	4227	1"	5/8"	150 min.	12249-12392, rec 1222' dsl mud
7-10-49	"	12239	8-3/4	4227	1"	5/8"	140 min.	12239-12425, rec 394' dsl mud.
7-17-49	"	12500	8-3/4	4227	1"	5/8"	40 min	12500-12561, rec 10' dsl mud.
8-6-49	"	12959	8-3/4	4227	1"	5/8"	46 min.	12959-12977, rec 15' dsl mud.
8-18-49	"	13139	8-3/4	4227	1"	5/8"	120 min.	13139-13228, rec 744 mud out w/ sulphur water

5-1/2" csg perforated:

9955-9975 w/ 8 shots per ft.
9600-9625 w/ 4 shots per ft.

