

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other Instructions
reverse side)

Form Approved
Project Number 10-11421
LEASE DESIGNATION AND SERIAL NO.
LC-067665
IF INDIAN, ALIQUOT OR TRACT NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.

1. TYPE OF WELL WELL ☒ OIL WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Amini Oil Corporation (K.K. Amini)	8. FIRM OR LEASE NAME Jackey-Federal
3. ADDRESS OF OPERATOR 400 Wall Towers West - Midland, Texas 79701	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 1980 FEL Section 1, T-9-S R-36-E	10. FIELD AND POOL, OR WILDCAT Aliso Pool
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4041 G.L.
	12. COUNTY OR PARISH Lea
	13. STATE N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
FIRST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(Other) ☐ (Note: Report results of multiple completion on Well Completion or Resumption of Flow Form)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data, including estimated date of starting, and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Plugging Procedure:

- Set 30 Plug @ 9550' and load hole with 9.5 Laden Fluid (Perforate 9623-28, 9630-35, 9638-42)
- Top of cement behind 4-1/2" casing 6000'
- Cut off 4-1/2" casing @ Free Point
- Set 25 sks. Plug @ cut off.
- Pull 4-1/2" casing
- Set 25 sks. Plug @ 4150 Bottom of 7-5/8" casing
- Pull 7-5/8" casing from 875'
- Set 25 sk. Plug @ 875'
- Set 10 sk. Plug in top of 10-3/4" casing
- Set marker and clean up location

AMENDMENT:

Place additional 25 sack plug in and out of shoe of surface casing at 416 feet.
Also, place additional 25 sack plug at 5,500 feet if 4 1/2" casing is pulled from below that depth.

I, the undersigned, certify that the foregoing is true and correct

Signature Arthur R. Brown TITLE Agent DATE 12-2-69

(This space is for Federal or State office use)

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED
DEC 4 1969
ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side