

NO. OF COPIES REQUESTED
DISTRIBUTION
SANTA FE
FILE
C.S.C.S.
LAND OFFICE
OPERATOR

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

1a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
1b. State Oil & Gas Lease No.
E-6859

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
SEE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
Marathon Oil Company	State E-6859-A
3. Address of Operator	9. Well No.
P.O. Box 220, Hobbs, New Mexico	1
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER <u>C</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM	Allison-Penn
THE <u>East</u> LINE, SECTION <u>2</u> TOWNSHIP <u>9S</u> RANGE <u>36E</u> N.M.P.M.	
11. Elevation (Show whether DF, RT, GR, etc.)	12. County
DF 4066'	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

13. Describe in brief the nature of proposed operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to plug and abandon this well per instructions and approved methods of the New Mexico Oil Conservation Commission commencing November 5, 1966.

The proposed plugging procedure is as follows:

TD 9731'. A cement retainer at 8400'. Squeeze with 15 sacks cement beneath retainer and leave 10 sacks cap on top of retainer, cut off 7" casing at approximately 6000', place a 30 sack cement plug in and out of the cut off 7" casing and a 30 sack cement plug at the top of the Tubb zone, a 30 sack cement plug at the top of the Abo zone, a 30 sack cement plug at the base of the San Andres zone, and a 40 sack cement plug across the 10-3/4" shoe at 4172'. A 20 sack cement plug will be placed at the surface in the 10-3/4" casing. All spaces between the plugs will be filled with mud laden fluids. A steel marker will be installed as per NMCCC specifications.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Chapman TITLE Area Supt. DATE 11-3-66

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: