	Budget Bureau No. 42–R368.4. Approval expires 12–31–60.
orm 9-831 a (Feb. 1951)	The Compose
(SUBMIT IN TRIPLICA	1 <i>1 E</i>)
UNITED STATE	S Lesse No. LC=069302
DEPARTMENT OF THE	
GEOLOGICAL SURV	ΈY
	·
SUNDRY NOTICES AND REP	ORTS ON WELLS
NOTICE OF INTENTION TO DRILL	
NOTICE OF INTENTION TO ANALYZE A	REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	REPORT OF RE-DRILLING OR REPAIR
	REPORT OF ABANDONMENT
	ARY WELL HISTORY
	·**-
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT	-
IEAROO III	c. P. O. Box 728
	w Mexico August 16 , 19 61
ell No. <u>1</u> is located <u>660</u> ft. from $\begin{cases} M \\ S \end{cases}$ line and	1980 4 from (E) 1: f
	The or sec?
(<u>/4</u> , NE/ <u>4</u> , Sec. 5 (<u>4</u> Bec. no.) (<u>7</u> wp.) (Range)	<u>NMPM</u>
Wildcat	(Meridian) New Mexico
(Field) (County or Subdivision)	(State or Territory)
e elevation of the derrick floor above sea level is 4099	ft
DETAILS OF WORI ate names of and expected depths to objective sands; show sizes, weights, and leng ing points, and all other important new	
ing points, and all other important prop	tns of proposed casings; indicate mudding jobs, cement- posed work)
e have plugged and abandoned subject well as f	
No casing was recovered.	
Spot plug No. 1, 40 sx, 12,370' to 12,470'. Spot plug No. 2, 45 sx, 11 485' to 11 585'	
Spot plug No. 2, 45 sx, 11,485' to 11,585'. Spot plug No. 3, 65 sx, 10,950' to 11,050'.	
Spot plug No. 4, 95 sx. 9.716 to 9.816	
Spot plug No. 4, 95 sx, 9,716, to 9,816, Spot plug No. 5, 60 sx. 9.094, to 9,194,	
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'.	
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'.	
Spot plug No. 4, 95 sx, 9,716 to 9,816 Spot plug No. 5, 60 sx, 9,094 to 9,194 Spot plug No. 6, 60 sx, 7,707 to 7,807 Spot plug No. 7, 60 sx, 6,900 to 7,000 Spot plug No. 8, 60 sx, 5,468 to 5,568 Spot plug No. 9 95 sx 4,105 to 1,205	
Spot plug No. 4, 95 sx, 9,716 to 9,816 Spot plug No. 5, 60 sx, 9,094 to 9,194 Spot plug No. 6, 60 sx, 7,707 to 7,807 Spot plug No. 7, 60 sx, 6,900 to 7,000 Spot plug No. 8, 60 sx, 5,468 to 5,568 Spot plug No. 9 95 sx 4,105 to 1,205	
 Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'. Spot plug No. 8, 60 sx, 5,468' to 5,568'. Spot plug No. 9, 95 sx, 4,105' to 4.205'. Spot 15 sx surface plug inside 13-3/8" OD causes of the strength of the strengt of	asing, installed 4" marker regulations. Cleaned location for
 Spot plug No. 4, 95 sx, 9,716 to 9,816. Spot plug No. 5, 60 sx, 9,094 to 9,194. Spot plug No. 6, 60 sx, 7,707 to 7,807. Spot plug No. 7, 60 sx, 6,900 to 7,000. Spot plug No. 8, 60 sx, 5,468 to 5,568. Spot plug No. 9, 95 sx. 4,105 to 4,205. 	asing, installed 4" marker regulations. Cleaned location for
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'. Spot plug No. 8, 60 sx, 5,468' to 5,568'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot 15 sx surface plug inside 13-3/8" OD ca extending 1' above ground level as per USGS USGS inspection. Plug and abandon completed 8. npany	asing, installed 4" marker regulations. Cleaned location for
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'. Spot plug No. 8, 60 sx, 5,468' to 5,568'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot 15 sx surface plug inside 13-3/8" OD ca extending 4' above ground level as per USGS USGS inspection. Plug and abandon completed 8	asing, installed 4" marker regulations, Cleaned location for -5-61, 11:00 A.M.
 Spot plug No. 4, 95 sx, 9,716* to 9,816*. Spot plug No. 5, 60 sx, 9,094* to 9,194*. Spot plug No. 6, 60 sx, 7,707* to 7,807*. Spot plug No. 7, 60 sx, 6,900* to 7,000*. Spot plug No. 8, 60 sx, 5,468* to 5,568*. Spot plug No. 9, 95 sx, 4,105* to 4.205*. Spot 15 sx surface plug inside 13-3/8* OD caretending 4* above ground level as per USGS USGS inspection. Plug and abandon completed 8. mpany	asing, installed 4" marker regulations, Cleaned location for -5-61, 11:00 A.M.
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'. Spot plug No. 8, 60 sx, 5,468' to 5,568'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot 15 sx surface plug inside 13-3/8" OD ca extending 1' above ground level as per USGS USGS inspection. Plug and abandon completed 8. npany TEXACO Inc. Hobbs, New Mexico H. N. Wade	asing, installed 4" marker regulations. Cleaned location for
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'. Spot plug No. 8, 60 sx, 5,468' to 5,568'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot 15 sx surface plug inside 13-3/8" OD care of the plug has been understand that the plan diverse approximation by the Geology of the second se	asing, installed 4" marker regulations, Cleaned location for -5-61, 11:00 A.M.
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'. Spot plug No. 8, 60 sx, 5,468' to 5,568'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot 15 sx surface plug inside 13-3/8" OD care of the plug has been understand that the plan diverse approximation by the Geology of the second se	asing, installed 4" marker regulations, Cleaned location for -5-61, 11:00 A.M.
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'. Spot plug No. 8, 60 sx, 5,468' to 5,568'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot 15 sx surface plug inside 13-3/8" OD care of the plug has been understand that the plan diverse approximation by the Geology of the second se	asing, installed 4" marker regulations, Cleaned location for -5-61, 11:00 A.M. AMMAA e Assistant District Superintendent
Spot plug No. 4, 95 sx, 9,716' to 9,816'. Spot plug No. 5, 60 sx, 9,094' to 9,194'. Spot plug No. 6, 60 sx, 7,707' to 7,807'. Spot plug No. 7, 60 sx, 6,900' to 7,000'. Spot plug No. 8, 60 sx, 5,468' to 5,568'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot plug No. 9, 95 sx, 4,105' to 4,205'. Spot 15 sx surface plug inside 13-3/8" OD care of the plug has been understand that the plan diverse approximation by the Geology of the second se	asing, installed 4" marker regulations, Cleaned location for -5-61, 11:00 A.M. AMMA AMMA e Assistant District Superintendent