



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 0-67771

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		<u>Dually Completed</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Federal Mills

February 2, 19 61

Well No. 1 is located 660 ft. from N line and 1980 ft. from E line of sec. 11

NW 1/4 Sec. 11
(1/4 Sec. and Sec. No.)

9-S
(Twp.)

36-E
(Range)

N47W
(Meridian)

Wildcat (Abe) & Allison Funn
(Field)

Lee
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 4063 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

9703' TD. The following evaluation was performed from July 15 through July 31, 1960. Ran GR-collar correlation log. Perf 7" csg w/4, 1/2" JNIP 8970-8990'. Ran Baker FB tension type packer on 2-7/8" tbg with 373' 2-7/8" tail pipe under packer and seating nipple on bottom. Set tbg at 9070', pkr at 8626' with 15,000# tension. Swabbed and tested. Spotted 500 gals MEC acid & washed perf. Set pkr w/18,000# tension. Pumped acid into formation. TP 4000-3000#. AIR 84 gpm. 10 min SI pressure 1000#. Swabbed & tested. Acidized same perfs w/1000 gals 15% NE acid. TP 2700#. AIR 168 gpm. Swabbed & tested. Killed well down tbg with water. Released Baker FB pkr & pulled 2-7/8" tbg & pkr. Reran 2-7/8" tbg w/Baker C-3 receptacle seal nipple, Garrett CV & seating nipple. Displaced water with 353 bbls Abe oil. Latched into Baker receptacle & set tbg in 14,000# tension. Pressure tested tbg w/1500# for 30 min. No drop. Opened Garrett CV below pkr. (continued on attached sheet)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Gulf Oil Corporation

Address Box 2167

Hobbs, New Mexico

By

Title Area Production Manager