## COPY

Suplement 1 Page #1

Forest Oil Corporation. Federal-Warren #1, Subsequent Report of Abandonment

This well was plugged in the following manner :

Halliburton Oil Well Cementing Co. pump spotted 50 sacks of cement from 9711' (P.B.T.D.) to 9549'-a 162' plug- through open end drill pipe.

The hole was muddled with 10# mud from 9549' to 4367'.

From 4367' in open hole to 4206' in the intermediate casing a 50 sack plug was spotted through open end drill pipe.

The hole was muddled with 10# mud from 4206' to 4000'.

At 4000' to 3919' a 25 sack plug or 81' of cement was spotted through drill pipe.

At 4000' a Baker Model "K" cast iron retainer bridging plug was set with 35,000# tension.

From 3919' to surface was filled with 10# drilling mud.

On top of the intermediate casing string is installed a swedge nipple on top of which is a 2" 4000# test plug value shut in.

In the top of the plug value is a swedge nipple into which is installed a  $4\frac{1}{2}$  OD permanent metal marker closed in on top which extends  $4.66^{\circ}$  above the ground level and which is painted with aluminum paint.

The cellar has been filled in, the pits covered and the location cleared of junk.

Enclosed are duplicate copies of the electric log run to total depth in this well by Schlumberger Well Surveying Corporation.

in e st meastrait

temphada is trigon from "I, stronger to the Abandonment of Abandonment

The weission physical is to following marner :

Palling the self competing Gee page djottel 50 cools of self frag. 2119 (Fee 1.2.) to SP(Stee 162) plune through open and sill tipe.

The second state of the 10 and from SEGA to 1800.

"mouth of the orac hole to L2069 in the internediate contract of grain a 50 grain. Due the original time of open end could experi-

The Los (Section 1991 Ser 401 Atter belbhur und sei 1968)

At LOADE to Still the 25 sect save on 011 of the structure to state of the structure of the

At 2007 - Laner Model "N" east into retailer inidmin plan was led with 35,600 - som br.

-Report of the SOL Shiw too Bit say applied of the source

úr ico — lo interniteie casimo soving is installed e lasdop ni la on tro — lo is d'iliot0" testo lagoesiye shut in.

The the top on the miner whise is a swedge ristic in the instanted of the checken and a second of the checken a a form of the tradition of all as there also add in on top with a stance of the above of a contract area which is painted with a second pairs.

de maier as nor filled in, ble pits severed not the location sienred of the location sienred of the l

irelos o a la llatte copie, or le electric lo; man ou actal lepth in 11's. Well a un orienter to Componation.