

NEW MEXICO
DUPLICATE

WELL RECORD

RECEIVED
COMMISSION

OIL CONSERVATION COMMISSION

HOBBS-OFFICE

..Depth Cleaned Out.....

RD OF DRILL-STEM AND SPECIAL T

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 9623 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing November 3, 1953

OIL WELL: The production during the first 24 hours was 207.5 barrels of liquid of which 99.8% was oil; % was emulsion; No % water; and .2% was sediment. A.P.I. Gravity 49.4°

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy. 2210	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates 2820	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres 4040	T. Granite	T. Dakota
T. Glorieta 5510	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo 7650	T.	T.
T. Permian Penn 8910	T.	T.
T. Rough 9604	T.	T.
T.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	248	248	Caliche & Sand				
248	457	209	Sand & Red Bed				
457	1600	1143	Red Bed				
1600	2042	442	Red Bed & Shells				
2042	2202	160	Red Shale & Sandy Shells				
2202	2567	365	Anhydrite, Shells & Sand Rock				
2567	2675	108	Shale & Shells				
2675	2821	146	Shale & Anhydrite				
2821	3454	633	Anhydrite, Shells & Salt				
3454	3633	179	Anhydrite				
3633	4191	558	Anhydrite & Shale				
4191	4456	265	Anhydrite & Gyp				
4456	4641	185	Anhydrite & Lime				
4641	7633	2992	Lime				
7633	8312	679	Lime & Shale				
8312	8630	318	Lime & Gyp				
8630	8640	10	Lime & Shale				
8640	8686	46	Lime				
8686	8988	302	Lime & Dolomite				
8988	9190	102	Lime & Shale				
9190	9555	375	Lime				
9555	9586	31	Core #1				
9586	9619	31	Core #2				
9619	9623	4	Core #3				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

January 22, 1954

(Date)

Company or Operator Magnolia Petroleum Company

Address Box 727, Kernit, Texas

Name E. H. Blundell

Position or Title District Superintendent