

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Stoltz, Wagner & Brown	8. Farm or Lease Name H. L. Vinson
3. Address of Operator P. O. Box 1714, Midland, Texas 79702	9. Well No. 1
4. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM East LINE, SECTION 22 TOWNSHIP 9-S RANGE 36-E NMPM.	10. Field and Pool, or Wellhead Crossroads Siluro Dev.
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Per verbal instructions of Mr. Sexton, we propose to plug as follows:
Set a cast iron plug at 12,235' with ~~10~~ 600 cement plug on top;
Cast iron plug at 9700' (Bough C Formation) with 35-ft. cement plug on top;
Shoot off casing at approximately 8610';
100-ft. cement plug at approximately 8610'; 100-ft. plug at top of Abo at 7710';
100-ft. cement plug across Glorieta at 5535';
100-ft. cement plug across bottom of 9-5/8" casing (half in and half out) at 4200';
100-ft. cement plug at top of the salt at 2190';
10 sax cement at the surface.
Place steel marker and clear location prior to requesting final inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>R. Bunker</u>	TITLE <u>Agent</u>	DATE <u>July 6, 1977</u>
APPROVED BY <u>John Bunker</u>	TITLE <u>Geologist</u>	DATE <u>11/11/77</u>

CONDITIONS OF APPROVAL, IF ANY:

Ex Jures 1/11/78

RECEIVED

SEP 11 1977

CL CONSTITUTION COMM.
HOBBS, N. M.