

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

JAN 8 1954

MISCELLANEOUS NOTICES

OIL CONSERVATION COMMISSION  
HOBBS-OFFICE

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	<b>X</b>
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Amarillo, Texas  
(Place)

1-6-54  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Oil Development Company of

Texas

SFPRR

Well No. 2-22

in M

(Company or Operator)

(Unit)

SW

1/4 SW

1/4 of Sec. 22

T. 9S

R. 36E

NMPM,

Crossroads-Penn

Pool

(40-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

A liner of 2447' of new 5 1/2" OD, 17#, N-80, SMS pipe and 3160' of new 17# J-55 will be run and hung with a Brown Type "C" liner hanger at 4068. The bottom of the liner will be at 9685.

200 Sxs. of cement will be spotted around the bottom of the liner and after allowing this to set 36 hours, a Baker Mod "K" retainer will be set at 4038 and the top of liner squeezed with 350 Sxs. of cement. After 48 hours, the retainer and cement will be drilled out and liner tested with 1200 psi for thirty minutes both before and after drilling the plug. This testing will be done on the 1-8-54 and will be under the supervision of Mr. A. O. Dry, Toolpusher for Sharp Drilling Co.

Approved JAN 8 1954, 19  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By *A. G. Stanley*  
Title Engineer District 1

Oil Development Company of Texas  
Company or Operator

By J. E. Hall

Position Engineer

Send Communications regarding well to:

Name Mr. E. A. Pagehal

Address 909 Polk St., Amarillo, Texas