NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico HOBBS 05 HOS 0. C. C.

MISCELLANEOUS NOTICES
Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Following is a Notice of Intention to do certain work as described below at the Gocory Mobil Oil Commany, Inc. Santa Fe Pacific Well No. In ME SW (Company or Operator) Jo Sec. To Santa Fe Pacific Well No. In Mellowere Subdivision Leaft-acre Subdivision County. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) TD: 12,231' Cag: 8 5/8" 5,000' w/3375 ax., 5½" liner 4,795-12,192' w/835 ax. Perfs: Open hole 12,192 - 12,231' Pronose to move in and rig up unit. Pull tubing 2,punc. Fun CP Collar log 11,600 - 12,231'. Farf. 5½" liner 12,176 - 12,166' w/1 JSFF (Schlumberger CR-) open hole log dated 10/29/57). Set Baker 'odel D pkr. w/expendable plug. Remove flapper valve in 5½" liner 312,188'. Run 2" the w/expendable plug. Remove flapper valve in 5½" liner 312,188'. Run 2" the w/expendable acidize perfs. 12,176 - 12,186' w/1000 gals 20% "F Acid. Swab test. Return to production from Devonian Perfs. and open hole section. Approved			Indicate Nature of No	tice by Ch	ecking Belo) ₩	
TO PLUG BACK NOTICE OF INTENTION SQUEEZE NOTICE OF INTENTION NOTICE OF						Notice of Intention to Drill Deeper	
TO SQUEEZE TO ADDIZE TO ADDIZE TO ADDIZE TO SCHOOL (Notice or Intention Of CHER) Notice or Intention (OTHER) Notice or Intention							
CONSERVATION COMMISSION Hobbs, New Yordco Jamery 20, 1964 Conservation Commission Hobbs, New Yordco Jamery 20, 1964 Conservation Commission Following is a Notice of Intention to do certain work as described below at the Sents Fe Pacific NE SW Company or Organy A of Sec. The Conservation of Section of Sectio					х		
ANTA FE, NEW MEXICO (Place) (Place) (Company of Ostal) Following is a Notice of Intention to do certain work as described below at the corony Mobil Oil Company, Inc. Sants Fe Pacific		X					
Continues: Following is a Notice of Intention to do certain work as described below at the Society Mobil Cil Company, Inc. Sants Fe Pacific		MISSION	Hobbs, New Me	::d:c o		Jamuary 20, 1964	
Well No. in Crossroads Devonian (Un Crossroads Devonian (Un Crossroads Devonian (Un Crossroads Devonian (Un No. Name (Pollow in Structions)) FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) TD: 12,231' Csg: 8 5/8" & 5,000' w/3375 sx., 5½" liner 4,795-12,192' w/835 sx. Perfs: Open hole 12,192 - 12,231' Propose to move in and rig up unit. Pull tubing & pump. Fun CT Collar log 11,600 - 12,231'. Farf. 5½" liner 12,176 - 12,186' w/1 JSFF (Schlumberger CR-vopen bole log dated 10/29/57). Set Beker 'bodel D pkr. w/expendeble plug. Remove flapper valve in 5½" liner 212,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 212,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 212,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble plug. Remove flapper valve in 5½" liner 312,186'. Run 2" the w/expendeble	Following is a Notice of I	ntention to do	certain work as described	i below at	the	8	
FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) TD: 12,231' Csg: 8 5/8" \$ 5,000' w/3375 sx., 5½" liner 4,795-12,192' w/835 sx. Perfs: Open hole 12,192 - 12,231' Propose to move in and rig up unit. Pull tubing a,pump. Fun CR Gollar log 11,600 - 12,231'. Ferf. 5½" liner 12,176 - 12,186' w/1 JSFF (Schlumberger GR-Vopen hole log dated 10/29/57). Set Reker Model D plan. W/sweendable plug. Remove flapper valve in 5½" liner \$12,188'. Run 2" thg. W/ckr and acidize perfs. 12,176 - 12,186' w/1000 gals 20% "F Acid. Swab test. Return to production from Devonian Perfs. and open hole section. Approved	OUTE OF OUR				. 	.Well Noin	• ·
FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) TD: 12,231' Csg: 8 5/8" \$ 5,000' w/3375 sx., 5½" liner 4,795-12,192' w/835 sx. Perfs: Open hole 12,192 - 12,231' Propose to move in and rig up unit. Pull tubing a,pump. Fun CR Gollar log 11,600 - 12,231'. Ferf. 5½" liner 12,176 - 12,186' w/1 JSFF (Schlumberger GR-Vopen hole log dated 10/29/57). Set Reker Model D plan. W/sweendable plug. Remove flapper valve in 5½" liner \$12,188'. Run 2" thg. W/ckr and acidize perfs. 12,176 - 12,186' w/1000 gals 20% "F Acid. Swab test. Return to production from Devonian Perfs. and open hole section. Approved	NE SW (Comp.	Sec	' 9 S , T, R	36 E	,NMPM.,	Crossroads Devonian	(Unit) P(
Approved DIL CONSERVATION COMMISSION Send Communications regarding well to: Name Name	11,600 - 12,231 CR-V open bole plug. Remove f acidize perfs.	log dated lapper va 12,176 -	$5\frac{1}{6}$ " liner 12,17 1 10/29/57). Set alve in $5\frac{1}{6}$ " liner 12,186° w/1000 g	6 - 12, Baker 3 12,1 als 205	,186' w/ Model D 188'. R ME Ac1	1 JSFF (Schlumberger pkr. w/expendable un 2" thr. w/pkr and d. Swab test. Return	
Approved Except as follows: By Croup Supervisor Position Send Communications regarding well to: Socony Mobil Oil Company, Inc. Name							
Approved OIL CONSERVATION COMMISSION By Croup Supervisor Position Send Communications regarding well to: Socony Mobil Oil Company, Inc. Name	A	4.		Socon			
Socony Mobil Oil Company, Inc. Name	Approved Except as follows:		4.0		od woldst	Oil Company, Inc.	
	Approvad			Ву	Croup S	Company or Operator	
Title				By	Croup S	Company or Operator 11 Original Company, Inc.	

Address....