## MAYO MARRS CASING PULLING INC. FIELD REPORT

NEW MEXICO OCD

ATTN: CHRIS WILLIAMS

30.025-03602

SANTA FE, PAÇIFIC

23-95-36e bb0/N 9 1980/N

WELL # 2 Unit M

Project: P & A

DATE 8-24-98

7-16-98

MIRU - RIH WITH TUBING - TAG PLUG @ 4550' - CLOSE IN WELL (8 HRS RIG)

VACATION FROM 7-17-98 THRU 7-26-98

7-27-98

POOH W/TBG - RIH WITH 4 1/2" BIT - RIG UP REVERSE UNIT - DRILLING FROM 3:00 PM TO 7:00 PM - PULL 10 STANDS - CLOSE IN WELL (11) (USE 260 BBLS WATER)

7-28-98

LOWER TUBING - START DRILLING - DRILL 12' - LAY DOWN SWIVEL - RUN TUBING TO 12,183' - SPOT 35 SXS CLASS C CEMENT - PULL 30 STANDS -CLOSE IN WELL

(12) (USE 380 BBLS WATER)

7-29-98

RIH WITH TBG AND TAG @ 12,183' - SPOT 25 SXS - POOH - WOC - LOWER TUBING - TAG @ 11,978' MIX MUD - POOH & SPOT 25 SXS @ 8810' -POOH WITH 50 JOINTS - CLOSE IN WELL (12)

7-30-98

MIX MUD - POOH & SPOT 35 SXS @ 4600' - POOH - WOC - TAG CEMENT @ 4480' - PULL TUBING TO 4400' - CLOSE IN WELL -(11)

7-31-98

MIX 240 SXS SALT GEL PER OCD - POOH & SPOT 45 SXS @ 1100' - POOH & SPOT 45 SXS @ 475' - POOH SPOT 15 SXS @ 30' TO SURFACE - CUT OFF WELLHEAD AND ANCHORS - INSTALL DRY HOLE MARKER - RIG DOWN (11)