


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

| | | | |
|--|-----------|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | XX | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | | |

March 31, 1949

Crossroads, N. M.

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Oil
Development Company of Texas Well No. 1-27 in the
Company or Operator C. S. M. of Sec. 27, T. 98, R. 36E, N. M. P. M.,
Crossroads Field, Lee County.

The dates of this work were as follows: March 28 and March 29 1949
Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on March 25 1949
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Tested the 9 5/8" casing with 1000 psi for 30 minutes before drilling the cement above the HOWCO multi-stage tool set at 3684.4' in the string; no pressure loss in 30 minutes. Tested the 9 5/8" casing before drilling the top float (on top of first joint) with 1000 psi for 30 minutes; no pressure drop. Drilled the float, shoe and over 3 ft. of cement below the shoe and tested again with 1000 psi for 30 minutes; there was no pressure drop. Casing contained cement from 3683 ft. to 4667 ft. Now drilling 8 3/4" hole below 5200 ft.

Witnessed by B. R. Allen G. P. Livermore, Inc Tool Pusher
Name Company Title

Subscribed and sworn before me this 31st

I hereby swear or affirm that the information given above is true and correct.

day of March 19 49
L. L. Drumheller Notary Public
Cochran County, Texas

Name L. J. Gude
Position Geologist & Engineer
Representing Oil Development Company of Texas
Company or Operator

My commission expires June 1 - 1949

Address 900 Polk St., Amarillo, Texas

Remarks:

APPROVED

Date Apr 1 1949

Ray Garbrough
Name

OIL CONSERVATION

11-

—

Youngberg Hall