	•	EW MEXICO  OUS NOTIC		مصنعه
Submit his notice in triplicate to the Oil Conservat			ייטפו צ דחת ו	naific
begin. A conv will be returned to the sender on wadvisable, or the rejection by the Commission or ag and work should not begin until approval is obtain the Commission.	which wil ent, of th ined. See	ll be given the appr he plan submitted. T e additional instruct	the part of the Hobbs - Office Hobbs	
	re of noti	te by checking below		
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	I		ENTION TO SHOOT OR TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS			ENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INT	ENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL				_
	Kex	mit, Texas	October 2, 19	1
		Place	Date	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico				
Gentlemen:				
Following is a notice of intention to do certain world				
Magnolia Petroleum Company Sent Company or Operator Lea	se			
of Sec. 29 , T. 9-8 , R. 36-8	1	N. M. P. M. Undesi	gnated (Penn, Pay)	
Loc County	y.			
FULL DETAILS O	y. F PRO	POSED PLAN O	F WORK	
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE	y. F PRO RULES A	POSED PLAN O	F WORK s of the commission	
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE :	y. OF PROD RULES A 832 w/B	POSED PLAN OF AND REGULATIONS	F WORK s of the commission Hanger, cemented w/	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE	y. OF PROP RULES A 332 w/B	POSED PLAN OF AND REGULATIONS	F WORK s of the commission Hanger, cemented w/	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE  Set 55381 of 5-1/2" Ext Liner 4094-96 heat. WCC 10 hrs. and 600 sax 64 gel.	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATIONS From Oil Tool ax mobilite, 12	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE:  84t 5538' of 5-1/2" Ext Liner 4094-96 heat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATIONS From Oil Tool ax mobilite, 12	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE:  84t 5538' of 5-1/2" Ext Liner 4094-96 heat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATIONS From Oil Tool ax mobilite, 12	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE:  84t 5538' of 5-1/2" Ext Liner 4094-96 heat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATIONS From Oil Tool ax mobilite, 12	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE:  84t 5538' of 5-1/2" Ext Liner 4094-96 heat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATIONS From Oil Tool ax mobilite, 12	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE:  84t 5538' of 5-1/2" Ext Liner 4094-96 heat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATIONS From Oil Tool ax mobilite, 12	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE:  84t 5538' of 5-1/2" Ext Liner 4094-96 heat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATIONS From Oil Tool ax mobilite, 12	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE:  Set 5538' of 5-1/2" Ext Liner 4094-96 heat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATIONS From Oil Tool ax mobilite, 12	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE :  Set 5538' of 5-1/2" Ext Liner 4094-96 neat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax Casing will be tested for shut off be	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATION OF COMMON OF THE COMMON OF TH	F WORK S OF THE COMMISSION Hanger, cemented w/ 20 neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE  Set 5538' of 5-1/2" Ext Liner 4094-96 neat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax  Casing will be tested for shut off be  Approved	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATION OF COMMON OF THE COMMON OF TH	F WORK s of the commission Hanger, cemented w/ to neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE  Set 5538' of 5-1/2" Ext Liner 4094-96 neat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax  Casing will be tested for shut off be  Approved	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATION OF COMMON OF THE COMMON OF TH	F WORK S OF THE COMMISSION Hanger, cemented w/ 20 neat, and 75 neat	125
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE  Set 5538' of 5-1/2" Ext Liner 4094-96 neat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax  Casing will be tested for shut off be  Approved	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATION From Oil Tool ax mobilite, 12 blug is drilled by By Position Dist	F WORK S OF THE COMMISSION Hanger, cemented w/ O neat, and 75 neat  Company or Operator  Company or Operator  Company or Operator	125 6 Gi:
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE :  Set 5538' of 5-1/2" Ext Liner 4094-96 neat, WOC 10 hrs. and 600 sax 6% gel, and 140 neat Circ. 40 sax, and 15 sax Casing will be tested for shut off be  Approved 0CT 4-1951 except at follows:	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATION From Oil Tool ax mobilite, 12 plug is drilled by Position Dist Send	F WORK S OF THE COMMISSION Hanger, camented w/ O neat, and 75 near Company or Operator Company or Operator Communications regarding	125 61: well
FULL DETAILS O FOLLOW INSTRUCTIONS IN THE :  Set 5538' of 5-1/2" Ext Liner 4094-96 heat, WOC 10 hrs. and 600 sax 6% gel, and 140 heat Circ. 40 sax, and 15 sax Casing will be tested for shut off be	F PROPERULES A 632 w/B 75 se	POSED PLAN OF AND REGULATION From Oil Tool ax mobilite, 12 plug is drilled by Position Dist Send	Petroleum Company Company or Operator  Communications regarding  Company of Company  Communications regarding  Company of Company  Communications regarding  Communications regarding	125 61: well

SAX.