


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

July 13, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation State CA Well No. 1 in the _____

Company or Operator

Lease

SE₄ SE₄ of Sec. 9, T. 10S, R. 36E, N. M. P. M.,

Wildcat Field, La County.

The dates of this work were as follows: June 25, to July 12, 1949

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on June 24, 19 49
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

13123' Total Depth, Line. 9876' DOD. Rigged up Howco. & ran 50 sacks El Toro cement and pumped to spot W/68½ bbl. mud flush, top of plug 9300' Pulled back to 4300' and ran 35 sacks El Toro cement & pumped to spot W/30½ bbl. mud flush, top of plug at 4160'. Pulled 58 joints of 8-5/8" OD. Csg. for 2000'. Spotted Cement plug from 1985' to 2020' with 30 sacks El Toro cement. Spotted top plug with 20 sacks El Toro cement from 22' to Surface. Put 4" pipe marker 5' above surface in center of top plug. Well plugged and abandoned 7-12-49.

Witnessed by K.V. Stephenson Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____

13th day of July 19 49

Will Hails Taylor

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Ray E. [Signature]

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Ray E. [Signature]
Name
Oil & Gas Inspector
Title

DATE JUL 18 1949