




Section 16

#2

T-11-S

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

(Company or Operator)

(Lease)

Well No. 2, in SE 1/4 of NE 1/4, of Sec. 16, T. 11-S, R. 38-E, NMPM.

Undesignated

Pool.

Loa

County.

Well is 1980' feet from North line and 660' feet from East line

of Section 16 If State Land the Oil and Gas Lease No. is OG-448

Drilling Commenced 6-22-57, 19..... Drilling was Completed 9-4-57, 19.....

Name of Drilling Contractor..... **Noble Drlg. Corporation**

Address 321 Pan American Building - Tulsa 3, Oklahoma

Elevation above sea level at Top of Tubing Head..... **3912' D.F.**..... The information given is to be kept confidential until
Not Confidential 19.....

OIL SANDS OR ZONES

Notes

No. 1, from.....to..... No. 4, from.....to.....

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet. _____

No. 2, from.....to.....feet.

No. 3, from.....to.....feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	36	New	320'	Guide	None		
8-5/8"	32-36#	NEW	6631	Guide	1690'		

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2"	13-3/8"	339'	275	Halliburton		
11	8-5/8"	6650'	1500	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

None - Dry Hole

Result of Production Stimulation..... **None - P&A**

..Depth Cleaned Out..

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special test or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 12,180 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing P & A, 19.
OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):
Schlumberger Tops. Southeastern New Mexico 12,142' Northwestern New Mexico

T. Anhy	2308'	T. Devonian		T. Ojo Alamo	
T. Salt	2348'	T. Silurian		T. Kirtland-Fruitland	
B. Salt	2963'	T. Montoya		T. Farmington	
T. Yates	3045'	T. Simpson		T. Pictured Cliffs	
T. Frank B Yates 3166'		T. McKee		T. Menefee	
T. Queen		T. Ellenburger		T. Point Lookout	
T. Grayburg		T. Gr. Wash		T. Mancos	
T. San Andres	4375'	T. Granite		T. Dakota	
T. Glorieta	5848'	T.		T. Morrison	
T. Frank B Yates Clearfork 6502'		T.		T. Penn	
T. Tubbs	7109'	T.		T.	
T. Abo	7797'	T.		T.	
T. Penn	9405'	T.		T.	
T. Miss	11530'	T.		T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	6'	6'	Cellar				
6	2308'	2302'	Sand, Shale				
2308'	2348'	40'	Anhy.				
2348'	2963'	615'	Salt, Anhy, Shale, Sand				
2963'	3045'	82'	Anhy				
3045'	4375'	1330'	Sand, Anhy, Shale, Salt				
4375'	5848'	1473'	Lim, Dolomite, Anhy.				
5848'	7797'	1949'	Dolomite, Anhy, Sand				
7797'	9065'	1268'	Dolomite, Anhy, Shale				
9065'	11063'	1998'	Lim, Shale				
11063'	11530'	465'	Lim, Sand, Shale				
11530'	12073'	543'	Lim, Chert, Shale				
12073'	12142'	69'	Shale				
12142'	12180'	38'	Dolomite				
	12180'		TD				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

September 9, 1957
Company or Operator Amerada Petroleum Corporation Address Roswell Star Route - Tatum, New Mex.
Name J. H. L. 28225 Position or Title Foreman