

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-11424.

3. LEASE DESIGNATION AND SERIAL NO.

NY01744

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal Brermand

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Allison, Penn.

11. SEC., T., R., E., OR SEER AND SURVEY OR AREA

Sec. 4, T-9-S, R-37-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

4022 GR

12. COUNTY OR PARISH

Lea

NY

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(Note: Report results of multiple completion on Well Completion or Recommendation Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

CASING PROGRAM: 10-3/4" csg. set @ 400' w/ 350 sks, cement circulated.
7-5/8" csg. set @ 4270' w/ 350 sks, top of cement at 8200'.
4-1/2" csg. set at 9703' w/ 375 sks, top of cement @ 7600'.

PERFORATIONS: 9630 to 9634 and 9641 to 9654.

PROPOSAL: (a) Spot 100' plug or 15 sks minimum plug across perforations.
(b) Cut and recover 4-1/2" csg. at 7400'.
(c) Spot 100' plug across stub of 4-1/2" csg and across Glorietta from approximately 5500-5600'.
(d) 100' plug 4220-4320' (7-5/8" casing shoe).
(e) Cut and recover 7-5/8" casing @ approximately 2900'.
(f) Spot 100' plug across stub of 7-5/8" csg. or anhydrite.
(g) 100' plug 350-450' (10-3/4" csg. shoe) & spot 20 sks plug at top of 10-3/4" csg., fill cellar and place marker.
(h) Mud will be used between plugs.
(i) All offset operators have been notified.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. L. Roschler

TITLE Geological Engineer

DATE August 25, 1965

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

ACTING DISTRICT ENGINEER