

(November 1983)
Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
P.O. BOX 700
HOLDS, NEW MEXICO 88240

SUBMIT IN TRIPLICATE*
(Other instruction
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-060581

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. T. Caudle

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Bagley - Penn.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T12S, R33E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER TA

2. NAME OF OPERATOR

Amerada Hess Corporation

3. ADDRESS OF OPERATOR

Drawer D, Monument, New Mexico 88265

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' TEL & 1980' FWL

14. PERMIT NO

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4258' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

XX

SUBSEQUENT REPORT ON:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plan to MIRU pulling unit. TIH w/work string & circ. hole w/mud. Perforate 5-1/2" liner at 5100'. Pump 50 sks. cement out perforation & leave 20 sks. inside csg. Pull up & spot 100' plug fr. 3765' - 3865'. Perforate 8-5/8" csg. at 375'. Pump 50 sks. cement out perforation & leave 20 sks. inside csg. Pull up & spot 10 sks. cement at surface. Remove well head, install dry hole marker & clean location.

* RESTORE LOCATION.

* PLEASE NOTIFY BLM.

RECEIVED
SEP 26 11 41 AM '89
CATTLE
HOLDS

18. I hereby certify that the foregoing is true and correct

SIGNED

R. E. Wheeler Jr.

TITLE

Supv. Adm. Svc.

DATE

9-22-89

(This space for Federal or State office use)

APPROVED BY

10/3/89 Adam Salas

TITLE

DATE

10/3/89

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.