

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

400000 10 31 JUN 23 10 31 AM '66

4. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

K-956 & K-5471

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator W. K. Byrom	8. Farm or Lease Name State B
3. Address of Operator P. O. Box 147 - Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER I, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 9 TOWNSHIP 10S RANGE 36E NMPM.	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4017 G. L.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-22-66: Permission requested to plug and abandon. We intend to place a 20 sack cement plug from 4989 to 4764 and shoot the 4-1/2" casing off. We will put a 15 sack plug at the point the casing is shot and a 10 sack plug at the bottom of the surface casing and a 15 sack plug at the top, with dry hole marker inserted. Location will be cleaned and anchors removed, as soon as pits dry.

*25 sacks of cement
15 sacks of cement
10 sacks of cement
15 sacks of cement
10 sacks of cement
15 sacks of cement
10 sacks of cement
15 sacks of cement
10 sacks of cement
15 sacks of cement*

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. K. Byrom TITLE Geologist DATE 6-22-66

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: