

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATES
(Other instructions on
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ **Subsidence disposal Dry**

2. NAME OF OPERATOR
BTA Oil Producers (Formerly W.E.K. Dry Co.)

3. ADDRESS OF OPERATOR
104 South Pecos, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
990' FSL & 660' FEL of Sec. 5, T-9-S, R-36-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4012' O.L.

5. LEASE DESIGNATION AND SERIAL NO.
MD 0449694

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR RANCH NAME
WEK

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Undesignated San Andres

11. SEC., T., R., OR B.L. AND SURVEY OR AREA
Sec. 5, T-9-S, R-36-E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☒
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐
FRACTURE TREATMENT	☐
SHOOTING OR ACIDIZING	☐
(Other)	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report (and Log form).)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zone depths pertinent to this work).*

Present Conditions:

T.D. 5022, P.B. 5013, 8-5/8" csg. @ 419 w/175 sx. (Circ)
4-1/2" csg. @ 5022 w/150 sx.

Perfs: 4914-70, 4835-55

Plugging Procedure:

Set CI Bridge Plug @ 4700' w/4 sx. cmt. on top
Cut & pull 4-1/2" csg.
Set 25 sx. cmt. on 4-1/2" csg. stub
Set 25 sx. cmt @ 419' (8-5/8" shoe)
Set 10 sx. cmt. @ surface
Install dry hole marker per NMOCC regulations

(Verbal approval by Art Brown - USGS - 3-4-70)

Formerly: WEK Dry Co. #1 WEK HARRIS

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE **Drilling Manager**

DATE **3-5-70**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

MAR 7 1970

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; and/or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1965 O-685229
GPO 8 37-499 867-651

APPROVED