

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO.
30-025-21954

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Bell "B"

8. Well No.

1

9. Pool name or Wildcat *Perm*
North Bagley (*Lower Penn*)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Tipperary Oil and Gas Corporation

3. Address of Operator

800 N. Marienfeld, Suite 100, Midland, Tx 79701

4. Well Location

Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line

Section 21

Township 11S

Range 33E

NMPM LEA

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4275.8 KB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spot 200 sx cement across 6245' for bottom plug if unable to get below suspected csg part at 6245'. After getting circulation, load hole with mud mixed at 25 sx gel per 100 bbls. Set 100' plug at 6245'. Cut 4 1/2" csg and pull as much as possible (+ 5000'). Set 100' plug 1/2 in and 1/2 out across the stub. WOC and tag. Set 100' plug 1/2 in and 1/2 out across 8 5/8" shoe (3750'). Cut 8 5/8" csg and pull as much as possible (+ 1000'). Set 100' plug 1/2 in and 1/2 out of stub. Set 100' plug across 13 3/8" shoe (385'). Set 10 sx plug at surface. Weld on dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

W. Jeffrey Sparks

TITLE

Engineer

DATE

11/21/94

TYPE OR PRINT NAME

W. Jeffrey Sparks

TELEPHONE NO. (915) 683-5203

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NOV 28 1994

1000 20 100

RECEIVED

NOV 23 1955

U.S. DEPT. OF
OFFICE