

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

FEB 14 1 04 PM '67

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K-3710	
7. Unit Agreement Name	
8. Farm or Lease Name	
Warren State	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Undes. North Bagley	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	
2. Name of Operator	
Stoltz & Company - Clark	
3. Address of Operator	
c/o Oil Reports & Gas Services, Box 763, Hobbs, New Mexico	
4. Location of Well	
UNIT LETTER G, 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 28 TOWNSHIP 11 S RANGE 33 E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	
4249 GR	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>
SUBSEQUENT REPORT OF:	
REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 1/28/67. Ran 13 3/8" 48# H-40 casing to 370 and cemented with 400 sacks Incor 2% Calcium Chloride. Plug down 5:00 A.M. 1/29/67. Cement circulated. WOC 18 hours and pressure tested with 600# for 30 minutes, test. O.K.

Ran 8 5/8" 24# & 32# J-55 casing to 3730 and cemented with 200 sacks Incor 2% Calcium Chloride and 2% gel. Plug down 4:30 P.M. 2/2/67. WOC 18 hours and pressure tested with 1000# for 30 minutes, test O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. L. Smith TITLE Agent DATE 2/14/67

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: