	-		Form C-103
DISTRIBUTION			Supersedes Old C-102 and C-103
SANTA FE	NEW MEXICO OIL CON	ERVATION COMMISSION	Effective 1-1-65
FILE	<u>.</u>		
U.S.G.S.	-	AY 2 10 40 AM '67	State X Fee.
LAND OFFICE	-{	AL LU HO AN OF	State 1 Fee 5. State Oil & Gas Lease No.
OPERATOR			E-9669
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			
I. OIL GAS WELL WELL	OTHER-		7. Unit Agreement Name
2. Name of Operator			8. Farm or Lease Name
Humble Oil & Refining	Company		N. Mex CC State
3. Address of Operator			9. Well No.
Box 1600, Midland, Tex	(as		2
4. Location of Well UNIT LETTER N	554 FEET FROM THE SOUTH	2086 FEET FRO	Java Fehn ATED
THE LINE, SECTI	10n 27 TOWNSHIP 10-S	AANGE 33-E	
	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County
	To be filed later		Lea
16. Check	Appropriate Box To Indicate N	lature of Notice, Report or O	ther Data
	NTENTION TO:	<u>. </u>	NT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	L	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	casing test and cement Joe [X] other Completion	ר־־ז
OTHER	[OTHEROMIDIE OF OIL	<u> </u>
OTHER			
17. Describe Proposed or Completed O	perations (Clearly state all pertinent det	ails, and give pertinent dates, including	ng estimated date of starting any proposed
work) SEE RULE 1103.			
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential	r cement plus 12% gel and light cement, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 g ot per ft. (14 shots). Max 4000 psi. AIR 4 BF	good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp M. ISIP Vacuum. Swabl 1 flowed 244 BO and 67	ent. Cemented @ 2500° /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/1 shot potted 1,000 gal 15%
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential	r cement plus 12% gel and light cement, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 g ot per ft. (14 shots). Max 4000 psi. AIR 4 BB L test dated 4-28-67, wel	good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp M. ISIP Vacuum. Swabl 1 flowed 244 BO and 67	ent. Cemented @ 2500°/ /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/l shot potted 1,000 gal 15% bed well and well began
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential	r cement plus 12% gel and light cement, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 g ot per ft. (14 shots). Max 4000 psi. AIR 4 BB L test dated 4-28-67, wel	good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp M. ISIP Vacuum. Swabl 1 flowed 244 BO and 67	ent. Cemented @ 2500° /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/1 shot potted 1,000 gal 15% bed well and well began
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential	r cement plus 12% gel and light cement, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 g ot per ft. (14 shots). Max 4000 psi. AIR 4 BB L test dated 4-28-67, wel	good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp M. ISIP Vacuum. Swabl 1 flowed 244 BO and 67	ent. Cemented @ 2500°/ /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/l shot potted 1,000 gal 15% bed well and well began
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential	r cement plus 12% gel and light cement, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 g ot per ft. (14 shots). Max 4000 psi. AIR 4 BB L test dated 4-28-67, wel	good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp M. ISIP Vacuum. Swabl 1 flowed 244 BO and 67	ent. Cemented @ 2500° /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/1 shot potted 1,000 gal 15% bed well and well began
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential	r cement plus 12% gel and light cement, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 g ot per ft. (14 shots). Max 4000 psi. AIR 4 BB L test dated 4-28-67, wel	good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp M. ISIP Vacuum. Swabl 1 flowed 244 BO and 67	ent. Cemented @ 2500° /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/l shot potted 1,000 gal 15% bed well and well began
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential	r cement plus 12% gel and light cement, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 g ot per ft. (14 shots). Max 4000 psi. AIR 4 BB L test dated 4-28-67, wel	good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp M. ISIP Vacuum. Swabl 1 flowed 244 BO and 67	ent. Cemented @ 2500° /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/l shot potted 1,000 gal 15% bed well and well began
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential choke. 567 MCF gas, 0	r cement plus 12% gel and light cament, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 got per ft. (14 shots). Max 4000 psi. AIR 4 BFL test dated 4-28-67, well GOR 2324, TP 400 psi. Ri	200 sx incor neat ceme good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp. M. ISIP Vacuum. Swabl flowed 244 BO and 67 g down unit. FRW.	ent. Cemented @ 2500° /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/1 shot potted 1,000 gal 15% bed well and well began
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential choke. 567 MCF gas, 0	r cement plus 12% gel and light cement, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 g ot per ft. (14 shots). Max 4000 psi. AIR 4 BB L test dated 4-28-67, wel	200 sx incor neat ceme good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp. M. ISIP Vacuum. Swabl flowed 244 BO and 67 g down unit. FRW.	ent. Cemented @ 2500°/ /2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/l shot potted 1,000 gal 15% bed well and well began
Drld 7 7/8" hole to 97 @ 9749' w/300 sx incor w/350 sx Halliburton 1 @ 2500'. Released rig Inst. BOP and ran tbg each 9678-9689 w/l sho NE acid across perfs. flowing. On potential choke. 567 MCF gas, 0	r cement plus 12% gel and light cament, circulated g @ 12:30 P. M., 4-21-67. to 9716'. Spotted 100 got per ft. (14 shots). Max 4000 psi. AIR 4 BFL test dated 4-28-67, well GOR 2324, TP 400 psi. Ri	200 sx incor neat ceme good cement. WOC 19 1, Set anchors and riggeral MCA acid. Perforate Log well. Ran tbg. Sp. M. ISIP Vacuum. Swabl flowed 244 BO and 67 g down unit. FRW.	/2 hours. Drld retainer ed up pulling unit. ed @ 9671-9673 w/1 shot potted 1,000 gal 15% bed well and well began

CONDITIONS OF APPROVAL, IF ANY