

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-103 and C-103  
Effective 1-1-65  
JUL 17 8 45 AM '67

6. Unit Agreement, Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	X-4667

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator PENNZOIL COMPANY	8. Field or Lease Name Harris State 17
3. Address of Operator 1007 Midland Savings Building Midland, Texas 79701	9. Well No. 1 <i>In the Perm</i>
4. Location of Well UNIT LETTER <u>E</u> <u>2130</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>17</u> TOWNSHIP <u>11-S</u> RANGE <u>34 E</u> NMPM.	10. Field and Pool, or Wildcat <b>UNDESIGNATED</b>
15. Elevation (Show whether DF, RT, GR, etc.) 4203.7 RKB	12. County Lea

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

#### NOTICE OF INTENTION TO:

#### SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-3-67 Drilled 77/8" hole to 9927-Ran Logs-Ran 232 jts.  
5 1/2" 17# N-80 casing to 9927'. Cement with 450  
sacks of Incor 50/50 DinMix. Plug down @ 6:00 a.m.  
5-3-67.

5-6-67 WOC 96 hours- Drilled out float cellar and cement  
inside bottom joint of 5 1/2" casing to 9925. Pressure  
to 2000 psi. No pressure drop in 30 mins.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Richard C. Stogd* TITLE Petroleum Engineer DATE 7/11/67

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: