

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-69, C.

APR 7 11 37 AM '67

APR 11 11 37 AM '67

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
K-5353

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Drilling Well		7. Unit Agreement Name -
2. Name of Operator Southern Minerals Corporation		8. Farm or Lease Name State "D"
3. Address of Operator P. O. Box 716 Corpus Christi, Texas		9. Well No. 1
4. Location of Well UNIT LETTER E , 1980 FEET FROM THE North LINE AND 510 FEET FROM West THE 8 LINE, SECTION 11-8 TOWNSHIP 34-E RANGE 34-E NMPM.		10. Field and Pool, or Wildcat UNDESIGNATED
15. Elevation (Show whether DF, RT, GR, etc.) 4195.6' Gr.		12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☒

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

March 30, 1967

Spudded in 4:00 P.M.. Drilled 17 1/2" hole to 373'. Set 372' of 13 3/8" casing. Cemented with 375 sacks of regular common cement with 2% Calcium Chloride. 20 sacks of cement circulated to surface. Plug on bottom at 11:00 P.M..

March 31, 1967

Waited on cement 18 hours (5:00 P.M.). Tested casing with 700# for 30 minutes. No pressure drop.

April 4, 1967

Drilled 11" hole to 4045'. Set 8 5/8" casing, 24# & 32#, J-55, ST&C, at depth of 4045'. Cemented with 250 sacks of Incor Neat plus 200 sacks of Incor with 2% Calcium Chloride. Plug on bottom at 5:25 A.M.. Calculated the top of the cement at 1700'.

Casing tested at 1000# with water for 30 minutes. Casing pressure after 30 minutes test was 980#.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Authorized Employee DATE April 7, 1967

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: