NO. OF COPIES RECEIVED DISTRIBUTION			Form C-103 Supersedes O		
SANTA FE FILE	The state of the s			C-102 and C-103 Effective 1-1-65	
U.S.G.S.	•		5a. Indicate Type	of Lease	
LAND OFFICE			State 🗶	Fee.	
OPERATOR	•		5. State Oil & Ga		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			HIIIII		
USE "APPLICATI	ION FOR PERMIT - 1 (FORM C-101) FOR ST	BACK TO A DIFFERENT RESERVOIR. JCH PROPOSALS.)	7. Unit Agreemen	t Name	
2. Name of Operator	OTHER-				
Gulf Oil Corporation				8. Form or Lease Name Lea "OR" State Com.	
3. Address of Operator P.O. Box 98; Andrews	, Texas 79714		9. Well No.	1	
4. Location of Well	60 South	2000	10. Field and Po	·	
UNIT LETTER,	FEET FROM THE South	LINE AND 1900 FEET F	ROM North Bagle	y Penn.	
THELINE, SECTION	9 TOWNSHIP 11-	RANGE 33-E NM	PM.		
	15. Elevation (Show whether	er DF, RT, GR, etc.)	- 12, County		
	4281' Gr.		Lea		
Check A	Appropriate Box To Indicate . ITENTION TO:		Other Data ENT REPORT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	AITER	ING CASING	
TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.		ND ABANDONMENT	
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB			
OTHER	·	OTHER			
17. Describe Proposed or Completed Opwork) SEE RULE 1103. RUPU on 8-24-70. Pulled y 10,026-28', 9989-91', 993 9632-34', 9534-36', 9509- 500 gal treater wtr. Ret mostly water. RUPU on 12 7700'. Ran tools & rolls 1375' 4 1/2", 13.01#, P-1 v/1# salt/ax fellowed v/2 menting complete at 9:30 in liner @ 6936'. Drills OK. Perferated 4 1/2" 11 10,127-29' v/2 HPF. Trea equipment & returned to p	preducing equipment. Per 39-41', 9916-18', 9878-6-11', 9391-93' & 9258-66 purmed well to producing 2-28-70. Pulled producing 3-28-70. Pulled producing 3-28-70. Pydril liner set 200 ax meat. Obtained a PM, 1-15-71. WOC 24 his dest in liner to 10,26 per 6 10,241-43', 10,22 per 6 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,241-43', 10,2	rforated 5 1/2" casing 30', 9810-12', 9780-82' 0'. Treated new perfs was status on 8-28-70. Was equipment. Discove Ram 8877' 4 1/2", 13.00 liner @ 10,261' & companies with 6200# v/34 rs. Ham temp survey. 61' FB. Tested liner tel-23', 10,176-78', 10, 201 156 FT. Such test	@ 10,084-86'; , 9703-05', 90 rith 500 gal 26 red damaged or hiff, N-80 FJ Hy mented w/100 sx left in 1: TSICT @ 5415', to 2000# for 30 160-64', 10,15	10,056-58', 663-65', 65 HE HCL & 4 tested maing @ approx dril liner & 6 16% Hi gel lacr. Ce- 7 Top cmt 7 min. Held 63-55' sad	
18. I hereby certify that the information	above is true and complete to the best	of my knowledge and belief.			
SIGNED	TITLE_	Area Engineer	DATE Janua	ry 30, 1971	
APPROVED BY	AND TITLE	TO PER MERCEN	DATE	3 1971	
CONDITIONS OF APPROVAL, IF ANY					

PE 21371
OIL COMMISSION COMMISSION
OIL COMMISSION COMMISSION
OIL COMMISSION COMMISSION
OIL COMMISSION COMMISSION
OIL COMMISSIO