

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANITARY		
FILE		
U.S.C.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

APR 17 8 25 AM '67

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E 7324	
7. Unit Agreement Name	
8. Farm or Lease Name	
State 24	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
UNDESIGNATED	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
The Louisiana Land and Exploration Company
3. Address of Operator
1605 Wilco Building, Midland, Texas
4. Location of Well
UNIT LETTER D, 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 24 TOWNSHIP 10-S RANGE 33-E NMPM.

15. Elevation (Show whether DF, RT, CR, etc.)
4195 gr. 4208 KB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPER. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spud 12:00 AM CST 4-5-67

Ran 12 jts new 13 3/8" 48# H-40 csg. Set @ 385' and cemented w/350 sx reg. w/2% CaCl. Circ. to surface. Plug down 11:05 AM 4-5-67. Test csg. to 500# PSI for 30 min. Tighten leak. Retest O. K. Ran 125 jts new 8 5/8" csg (32# - 28# - 24#). Set @ 4016' & cemented w/200 sx Incor 50-50 Poz, 2% gel, 4# salt/sx & 100 sx Incor Neat w/4# salt/sx & 2% CaCl. Plug down 4:45 PM 4-11-67. WOC/24 hrs. Test csg. to 1200#. Test O. K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Peck Hardee, Jr.

TITLE Petroleum Engineer

DATE April 14, 1967

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: