NO. OF COPIES RECEIVED	Francis 100
DISTRIBUTION	Form C-103 Supersedes Old
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION	OF F1-102 and C-103 Effective C1-C
FILE	Ellective VI-60
U.S.G.S. Jun 16	50 IRCcat Lyce of Lease
LAND OFFICE	State X Fee
OPERATOR	5. State Oil & Gas Lease No.
	NM-315
SUNDRY NOTICES AND REPORTS ON WELLS	mmmmiliik
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1.	7. Unit Agreement Name
OIL GAS OTHER-	
2. Name of Operator	8. Farm or Lease Name
TEXAS PACIFIC OIL COMPANY	J. P. Collier
3. Address of Operator	9. Well No.
P. O. Box 1069 - Hobbs, New Mexico	4Y
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER G 1980 FEET FROM THE NOTTH LINE AND 2005 FEET FROM	Undesignated
LINE AND FEET FROM	
THE East LINE, SECTION 10 TOWNSHIP 11-S RANGE 33-E NMPM.	
TOWNSHIP RANGE DOWNSHIP	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4257.7° GR	Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Otl	
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JQB OTHER	ALTERING CASING PLUG AND ABANDONMENT
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. 1. Drilled to 3826. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @	
 Drilled to 3826'. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @ Cemented w/550 sks. 50-50 pozmix + 4% Gel: 150 sks. Reg. + 1% 	3823. CA CL ₂ .
1. Drilled to 3826. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @	3823. CA CL ₂ .
 Drilled to 3826'. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @ Cemented w/550 sks. 50-50 pozmix + 4% Gel: 150 sks. Reg. + 1% 	3823. CA CL ₂ .
 Drilled to 3826. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @ Cemented w/550 sks. 50-50 pozmix + 4% Gel; 150 sks. Reg. + 1% Pumped plug to 5777. WOC 18 hrs. Ran Temp. Survey. T.C235 	3823. CA CL ₂ .
 Drilled to 3826. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @ Cemented w/550 sks. 50-50 pozmix + 4% Gel; 150 sks. Reg. + 1% Pumped plug to 5777. WOC 18 hrs. Ran Temp. Survey. T.C235 	3823. CA CL ₂ .
 Drilled to 3826. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @ Cemented w/550 sks. 50-50 pozmix + 4% Gel; 150 sks. Reg. + 1% Pumped plug to 5777. WOC 18 hrs. Ran Temp. Survey. T.C235 	3823. CA CL ₂ .
 Drilled to 3826. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @ Cemented w/550 sks. 50-50 pozmix + 4% Gel; 150 sks. Reg. + 1% Pumped plug to 3777. WOC 18 hrs. Ran Temp. Survey. T.C235 	3823. CA CL ₂ .
 Drilled to 3826. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @ Cemented w/550 sks. 50-50 pozmix + 4% Gel; 150 sks. Reg. + 1% Pumped plug to 5777. WOC 18 hrs. Ran Temp. Survey. T.C235 	3823. CA CL ₂ .
 Drilled to 3826. Ran 119 jts. 9-5/8" 36# J-55 Casing. Set @ Cemented w/550 sks. 50-50 pozmix + 4% Gel; 150 sks. Reg. + 1% Pumped plug to 3777. WOC 18 hrs. Ran Temp. Survey. T.C235 	3823. CA CL ₂ .

Original Signed by

Signed Sheldon Ward TITLE Area Superintendent DATE 6-14-67

APPROVED BY DATE DATE DATE