NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
0.000	-	1

## HOBBS OFFICE Q. C. C.

Form C-103 Supersedes Old C-102 and C-103

SANTA FE	NEW MEXICO OIL CONSERVATION COMMUSSION	Effective 1-1-65
FILE	Control of the contro	5a. Indicate Type of Lease
U.S.G.S.		State Fee.
OPERATOR		5. State Oil & Gas Lease No. OG-5083
		mmmmmmv
SUNDR	Y NOTICES AND REPORTS ON WELLS  POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  ION FOR PERMIT _" (FORM C-101) FOR SUCH PROPOSALS.)	
OIL GAS WELL	OTHER-	7. Unit Agreement Name Flying M (SA)
2. Name of Operator States Gas P	roducing Company	8. Form or Lease Name Flying M (SA) Unit Tr 16
3. Address of Operator P. 0. Box 235, Midl	and, Texas 79701	9. Well No. 3
4. Location of Well	659.3 south 1985.4	10. Field and Pool, or Wildcat Flying "M" (San Andres)
east	PEET FROM THE LINE AND FEET FR	
THELINE, SECTI	ON TOWNSHIP RANGE NMF	<del>- munimikkikki</del>
	15. Elevation (Show whether DF, RT, GR, etc.) 4344.1	12. County Lea
All Charles	Appropriate Box To Indicate Nature of Notice, Report or C	Other Data
	NTENTION TO: SUBSEQUE	NT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	
OTHER	OTHER	
•	perations (Clearly state all pertinent details, and give pertinent dates, includ	ing estimated date of starting any proposed
17. Describe Proposed or Completed C work) see Rule't fos.	perations (Clearly state an permitting actions, and good positions	•
SPUD DATE: 4:00 p.m.	6-7-67	
Ran 9 jts 8	-5/8" OD, 8rd, 24#, R-2, J-55, Cond. "B" casing	g set at 295'. Cemented
	cks Lone Star Class "A"with 2% CaCl. Cement cond casing with 1000#, held OK. WOC 14 hours.	irculated. PD at 11:45
p.m. leste	d casing with 1000%, held ox. woo 14 hours.	
CASING WAS CEMENTED WIT	TH OPTION NO. 2 AS FOLLOWS:	
1. Volume of cement sl	urry - 300 cubic feet.	
	cement with 2% CaCl.	
3. Approximate tempera	ture of slurry - 84°. Formation temperature - 95°.	
<ol> <li>Estimated minimum f</li> <li>Estimate of cement</li> </ol>	strength at time of testing - 1020# per sq. in	ch.
6. Actual time cement	in place, prior to starting cement test - 14 h	ours.
18. I hereby certify that the informati	on above is true and complete to the best of my knowledge and belief.	
IN P. Havin	Division Production Supt.	June 14, 1967
APPROVED BY	TITLE	DATE
CONDITIONS OF APPROVAL, IF A	W.	