NO. OF COPIES RECEIVED		Form C-193
DISTRIBUTION		Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE		
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE		State X Fee
OPERATOR		5. State Oil & Gas Lease No.
	<b>~</b> 	K-1111
SUNDR	RY NOTICES AND REPORTS ON WELLS	
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO CRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT _" (FORM C-101) FOR SUCH PROPOSALS.)		
1		7, Unit Agreement Name
WELL X WELL	OTHER-	
2. Name of Operator		8. Farm or Lease Name
The Superior Oil Company		State E
3. Address of Operator		9. Well No.
Box 1900, Midland,	Texas 79701	1
4. Location of Well		10. Feet and Dock LACIES
М	660 FEET FROM THE South LINE AND 660	UNDES (GIVATED
UNIT CEFFER	FEET FROM THE DOUCH LINE AND FEET FR	Middle Lane-Penn.
West	13 10-6 22 5	
THE WEST LINE, SECTION	ON 13 TOWNSHIP 10-S RANGE 33-E NMF	эм. (
mmmmmm	15. Elevation (Show whether DF, RT, GR, etc.)	
		12. County
16.	4213 DF, 4216 RKB	Lea
Check A	Appropriate Box To Indicate Nature of Notice, Report or (	Other Data
NOTICE OF IN	バイビバイ(ヘ)、 イベ・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・	NT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANCONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB X	TOO ARE ABARDONMENT
	OTHER	
OTHER		
work) SEE RULE 1103.	perations (Clearly state all pertinent details, and give pertinent dates, includi	ng estimated date of starting any proposed
Drilled 7-7/8" hole	e to 9864 feet. Ran $4-1/2$ " $11.60\%$ N-80 and J-5	5 LT&C casing to 9864
feet. Cemented wit	th 200 sacks Incor Pozmix A cement. Completed	at 1:11 A.M. August 1
1967. Ran temperat	ture survey and survey showed cement at 9300 fe	et outside 4-1/2"
casing. Installed	tubing head, tested casing to 2200 psi for 30	minutes OK NOC 24
hours. Ran bit and	scraper on 2-3/8" tubing to top of cement plu	or at 9800 feet
Circulated 1 hour a	and pulled out of hole. Perforated Bough "C" i	nterval 973/1-/8 after
total WOC 36 hours.	Set Baker Model "D" packer at 9690 feet on w	vira line Pan 2.2/01
tubing and latched	into packer. Swabbed well in and kicked off,	flering August / 1067
22218 200 2000	into packer. Dwadded well in and kicked off,	riowing August 4, 1967.
	•	
18. I hereby certify that the information	above is true and complete to the best of my knowledge and belief.	
SIGNED NV Surveye	O. V. Sivage Production Engineer	DATE August 11, 1967
	1116	DATE
APPROVED ST		
	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY;		