

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-3983

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Major, Giebel & Forster	8. Farm or Lease Name Shell State
3. Address of Operator 1126 Vaughn Building, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>22</u> TOWNSHIP <u>10-S</u> RANGE <u>33-E</u> NMPM.	10. Field and Pool, or Wildcat Inbe
15. Elevation (Show whether DF, RT, GR, etc.) 4223 KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set cast iron bridge plug 20' above perforation; Perf 9742-51

2 sxs cement top of plug.

25 sxs cement stub of 5-1/2" casing

25 sxs at 5312' - Top Glorietta

40 sxs shoe 8-5/8"

If 8-5/8" casing Pulled:

25 sxs stub 8-5/8"

25 sxs shoe of 12-3/4"

10 sxs at surface

If 8-5/8" casing not pulled:

10 sxs at surface 8-5/8"

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Engineer DATE July 26, 1971

APPROVED BY [Signature] TITLE SUPERVISOR DISTRICT I DATE JUL 28 1971

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUL 27 1971

OIL CONSERVATION COMM.
HOUSTON, TEXAS