

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K 5558
7. Unit Agreement Name
8. Farm or Lease Name State "D"
9. Well No. 1
10. Field and Pool, or Wildcat Vada (Penn)
12. County Lea

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator MARALO, INC.
3. Address of Operator P. O. Box 832, Midland, Texas 79701
4. Location of Well UNIT LETTER L, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 9-S RANGE 34-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4288 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well to be plugged as per verbal instructions of Mr. John Runyan as follows:

Cast Iron Bridge Plug @ 9700' with 20' cement on top of plug; 100' cement in and out of 5-1/2" stub - 100' cement plug top of Glorieta, approximately 5395'; 100' cement in and out 8-5/8" - 100' @ 2163'; 10 sx at surface w/dry hole marker. Mud to be used between cement plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Guadalupe Hamon</u>	TITLE <u>Production Clerk</u>	DATE <u>4/13/76</u>
APPROVED BY _____	TITLE _____	DATE <u>APR 19 1976</u>
CONDITIONS OF APPROVAL, IF ANY:		