

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K 5558
7. Unit Agreement Name
8. Farm or Lease Name State "D"
9. Well No. 2
10. Field and Pool, or Wildcat Vada (Penn)
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER- ☐

2. Name of Operator
MARALO, INC.

3. Address of Operator
P. O. Box 832, Midland, Texas 79701

4. Location of Well
UNIT LETTER E, 2130 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 9-S RANGE 34-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
4276 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well plugged as per verbal instructions of Mr. John Runyan on April 29, 1976 as follows:

Cast Iron Bridge Plug set @ 9675' with 35' cement on top of plug; 1st cement plug - 25 sx @ 4608' - 4491'; 2nd cement plug - 35 sx @ 4041' - 3919'; 3rd cement plug - 35 sx @ 2250' - 2126'; 4th cement plug - 10 sx @ surface. Drilling Mud used between cement plugs and Dry Hole Marker set at surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Marina Hansen TITLE Production Clerk DATE May 5, 1976

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: