

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| |
|--|
| 5a. Indicate Type of Lease |
| State <input checked="" type="checkbox"/> Fee <input type="checkbox"/> |
| 5. State Oil & Gas Lease No. |
| E-8447-1 |

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|--|---|
| 1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- | 7. Unit Agreement Name |
| 2. Name of Operator Gulf Oil Corporation | 8. Farm or Lease Name Lea FH State |
| 3. Address of Operator Box 670, Hobbs, New Mexico 88240 | 9. Well No. 1 |
| 4. Location of Well UNIT LETTER <u>N</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1836</u> FEET FROM THE <u>West</u> LINE, SECTION <u>18</u> TOWNSHIP <u>11-S</u> RANGE <u>34-E</u> NMPM. | 10. Field and Pool, or Wildcat Inbe Permo Penn |
| 15. Elevation (Show whether DF, RT, GR, etc.) 4203' GL | 12. County Lea |

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

Plugged and abandoned

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9920' TD, 9904' PB.

Pulled tubing. Ran cement retainer on 2-3/8" tubing and set at 7950'. Squeezed perforations 9869' to 9875' with 35 sacks of Class H cement below retainer. Squeezed to 5000#. Loaded hole with 180 barrels of water containing 45 sacks of gel. Spotted 50' cement plug on top of retainer. Cut and recovered 5-1/2" casing at 5300'. Spotted 20 sack cement plug from 5350' to 5250', across 5-1/2" stub at 5300'. Spotted 30 sack cement plug from 4050' to 3950', across 8-5/8" shoe at 4000'. Cut and recovered 8-5/8" casing from 1018'. Spotted 50 sack cement plug from 1068' to 968', across 8-5/8" stub at 1018'. Spotted 72 sack cement plug from 410' to 310', across 13-3/8" shoe at 360'. Spotted 38 sack cement plug from 50' to surface. Installed dry hole marker. Plugged and abandoned February 20, 1975. Will advise when location is ready for your final inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. J. Danbury

TITLE Area Engineer

DATE February 20, 1975

APPROVED BY Eddie W. Long

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OIL & GAS

MAR 28 1975

RECEIVED

FEB 2 1973

OIL CONSERVATION COMM.
MOBES. N. M.