

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1103.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1986	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt		T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
T. Salt		T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	2647	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers		T. Devonian	T. Menefee	T. Madison
T. Queen		T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg		T. Mantoya	T. Mancos	T. McCracken
T. San Andres	3900	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	5365	T. McKee	Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	T.
T. Blinbry		T. Gr. Wash	T. Morrison	T.
T. Tubb	6853	T. Granite	T. Todilto	T.
T. Drinkard		T. Delaware Sand	T. Entrada	T.
T. Abo	7710	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	8957	T.	T. Chinle	T.
T. Penn.		T.	T. Permian	T.
T. Cisco (Bough C)	9837	T.	T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1986	1986	Red beds				
1986	2636	650	Red beds, anhydrite & salt				
2636	2773	137	Sandy shale & anhydrite				
2773	3900	1127	Anhydrite & salt				
3900	4640	740	Dolomite & Anhydrite				
4640	5249	609	Lime				
5249	5365	116	Dolomite & Anhydrite				
5365	7710	2345	Dolomite, sand & shale				
7710	8270	560	Red & green shale				
8270	8957	687	Shale & dolomite				
8957	9896	939	Lime & shale				
No cores or tests taken.							