

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
OG - 4898	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Cayman Corporation	8. Farm or Lease Name Murphy State
3. Address of Operator 1206 Wilco Building, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>0</u> , <u>1980</u> FEET FROM THE <u>East</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>13</u> TOWNSHIP <u>10-S</u> RANGE <u>33-E</u> NMPM.	10. Field and Pool, or Wildcat Inbe - Permo Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4199' RT	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-27-72 Set cast iron bridge plug at 9800' with 2 sacks cement on it.

11-30-72 Shot into and recovered 4477' of 5 1/2" 17# casing. Placed 40 sack cement plugs at 4490' and at 4000'

12-8-72 Shot into and recovered 1283' of 8 5/8" 24# casing. Placed 50 sack cement plugs at 1300' and at 420'. Then set 10 sack cement plugs at surface.

Installed marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John W. Goodrich TITLE Engineer DATE 12-29-72

APPROVED BY John W. Runyan TITLE Geologist DATE FEB 11 1977

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION COMM.
HOBBES, N. H.

JAN 2 1978

RECEIVED