

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-22272

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
K 4280

7. Lease Name or Unit Agreement Name

Warren 27 State

8. Well No.
1

9. Pool name or Wildcat Permian
Bagley N. (Wolfcamp)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Tom Brown, Inc.

3. Address of Operator
P. O. Box 2608, Midland, Texas 79702

4. Well Location
Unit Letter L : 1980 Feet From The south Line and 510 Feet From The west Line

Section 27 Township 11 S Range 33 E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4249' GR 4259' DF

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Casing: 8 5/8" @ 3765' Cement circulated to surface.
5 1/2" @ 10,062' TOC 7400' (temperature survey)

Abandoned Perfs: 9402-24' CIBP @ 9366' w/2sxs cmt. CIBP @ 8725' w/2 sxs cmt.

Existing Wolfcamp perforations: 8368-78'.

Proposed P&A: 1. Set CIBP @ 8340' w/10 sxs cmt.
2. Cut casing at +7000' and pull. Set 35 sx plug (50' in and 50' out of csg. stub) @ csg. stub. TAO P&A
3. Set 40 sx plug @ 5120'.
4. Set 40 sx plug from 3810 to 3760' (50' in and 50' out) TAO P&A
5. Set 40 sx plug at 1750'.
6. Set 10 sx plug at surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve L. Thomson TITLE Operations Manager DATE 08/31/89

TYPE OR PRINT NAME Steve L. Thomson TELEPHONE NO. 915/682-9715

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

SEP 7 1989

USE AND CORRECTIVE 1014 P&A
WITH 2511 GR / APPROVED